

R48 系列高压大流量不锈钢减压阀

(R48 Series High Pressure And Large Flow Stainless Steel Pressure Reducer)

R48系列不锈钢减压器,采用大口径活塞式结构,输出压力高,压力稳定,适用于高压大流量场合。

R48 series stainless steel pressure reducer adopts large diameter piston structure, high output pressure and stable pressure, suitable for high pressure and large flow occasions.



产品特点 Features

- ⊙ 输入压力高, 出口流量大
- ⊙ 活塞设计, 安全可靠性能高
- ⊙ 平衡阀芯设计
- ⊙ High input pressure and large outlet flow
- ⊙ Piston design, high safety and reliability
- ⊙ Balanced valve core design

特性参数 Operating Parameters

- ⊙ 进出气接口: 3/4"、1"NPT
 - ⊙ 最大进口压力: 6000Psi
 - ⊙ 输出压力范围: 50-1500, 50-4000Psi
 - ⊙ 工作温度: -40至74°C
 - ⊙ CV值: 2.0
 - ⊙ Air inlet and outlet interface: 3/4"、1"NPT
 - ⊙ Max inlet pressure: 6000Psi
 - ⊙ Output pressure range: 50-1500, 50-4000Psi
 - ⊙ Working temperature: -40~74°C
 - ⊙ CV value: 2.0
- ⊙ 材质:
- 阀体: 316L
 - 阀芯: 316L
 - 阀座: PCTFE
 - O型圈: VITON
 - 其余部件: 304
- ⊙ Material:
- Valve body: 316L
 - Spool: 316L
 - Valve seat: PCTFE
 - O-rings: VITON
 - Rest of the parts: 304

订购指南 Ordering Information

系列 Series	阀座材料 Valve seat material	进口压力 Import pressure	出口压力 Outlet pressure	进气接口 Intake port	出气接口 Airoutlet	选项 Options
R44	P	A	C	00	00	P
	C:PCTFE	A:6000psi	C:1500psi D:4000psi	00:3/4NPT (F) 01:1"NPT(F) 11:3/4卡套接头 12:3/4焊接接头 其他接头可选	00:3/4NPT (F) 01:1"NPT(F) 11:3/4卡套接头 12:3/4焊接接头 其他接头可选	P:带面板安装