

781-不剥胶高压液压软管

Non-peeling high pressure hydraulic hose



- 软管结构: 合成橡胶内层, 4层或6层高强度钢丝缠绕增强层, 耐磨耐天候黑色合成橡胶外层。
- 应用: 超高压状况, 用于石油基液压油, 水乙二醇, 润滑剂和水。
- 适配接头: 派克不剥胶一体式接头
- SAE 100 R13, EN 856-R13
- 适配接头: 扣压式78系列
- 温度范围: -40°C~+125°C
- 空气: 最高+70°C, 水: 最高+85°C

- Hose construction: synthetic rubber inner layer, 4 or 6 layers of high-strength steel wire spiral reinforcement layer, wear-resistant and weather-resistant black synthetic rubber outer layer.
- Application: Ultra-high pressure conditions, for petroleum-based hydraulic oil, water glycol, lubricants and water.
- Adapter: Parker non-peeling one-piece connector
- SAE 100 R13, EN 856-R13
- Adapter: Crimp 78 series
- Temperature range: -40°C~+125°C
- Air: up to +70°C, water: up to +85°C

							#	
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
20	3/4	19.1	32.0	140.0	240	1.59	781-12	HH078112P
25	1	25.4	35.0	140.0	300	2.20	781-16	HH078116P
32	1 1/4	31.8	35.0	1403.0	420	3.69	781-20	HH078120P
40	1 1/2	38.1	35.0	140.0	500	4.79	781-24	HH078124P

791TC-不剥胶高压液压软管

Non-peeling high pressure hydraulic hose



- 软管结构: 四或六层高强度钢丝缠绕增强层, 耐油合成橡胶内层, 耐油耐磨耐天候黑色合成橡胶外层。
- 应用: 用于石油基液压油、润滑油、水乙二醇、乳化液、原油、燃油和水。
- 适配接头: 派克不剥胶一体式接头
- SAE 100 R15, ISO 3862-1 R15
- 适配接头: 扣压式79系列
- 温度范围: -40°C~+125°C
- 空气: 最高+70°C, 水: 最高+85°C

- Hose structure: Four or six layers of high-strength steel wire spiral reinforcement layer, oil-resistant synthetic rubber inner layer, oil-resistant, wear-resistant and weather-resistant black synthetic rubber outer layer.
- Application: For petroleum-based hydraulic oil, lubricating oil, water glycol, emulsion, crude oil, fuel and water.
- Adapter: Parker non-stripping one-piece connector
- SAE 100 R15, ISO 3862-1 R15
- Adapter: Crimp 79 series
- Temperature range: -40°C~+125°C
- Air: up to +70°C, water: up to +85°C

							#	
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
20	3/4	19.1	42.0	168.0	200	1.59	791TC-12	HH079112
25	1	25.4	42.0	168.0	250	2.20	791TC-16	HH079116
32	1 1/4	31.8	42.0	168.0	250	3.69	791TC-20	HH079120
40	1 1/2	38.1	42.0	168.0	305	4.49	791TC-24	HH079124