



ARGUS 1TE/R6 HF-棉线低压管

Cotton thread low pressure tube

- 软管结构: 一层高抗拉纤维编织层, 耐油合成橡胶内层, 耐磨损、臭氧、碳氢化合物合成橡胶外层。
- 应用: 低压液压管道 (液压油、防冻剂、空气和水), 特为插入自锁式接头而制, 环保材料。
- 适配接头: 两件式编织类扣压接头
- SAE 100R6, EN 854 R6
- 温度范围: -40°C~+100°C
- 空气: 最高+70°C

- Hose structure: one layer of high tensile fiber braid, oil-resistant synthetic rubber inner layer, wear, ozone, hydrocarbon resistant synthetic rubber outer layer.
- Application: low-pressure hydraulic pipeline (hydraulic oil, antifreeze, air and water), specially made for insertion into self-locking connectors, environmentally friendly materials.
- Adapter: two-piece braided crimp connector
- SAE 100R6, EN 854 R6
- Temperature range: -40°C~+100°C
- Air: up to +70°C

								#	
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code	
6	1/4	6	12.7	2.8	11	64	0.13	1TEHF-04	SH710004
8	5/16	8	14.3	2.8	11	76	0.13	1TEHF-05	SH710005
10	3/8	10	15.9	2.8	11	76	0.17	1TEHF-06	SH710006
12	1/2	13	19.8	2.8	11	102	0.23	1TEHF-08	SH710008
16	5/8	16	23.0	2.4	10	107	0.27	1TEHF-10	SH710010
20	3/4	19	26.9	2.1	8	152	0.37	1TEHF-12	SH710012
25	1	25	33.4	1.9	7	203	0.49	1TEHF-16	SH710016



ARGUS 2TE HF-棉线低压管

Cotton thread low pressure tube

- 软管结构: 一层高抗拉纤维编织层, 耐油合成橡胶内层, 耐磨损、臭氧、碳氢化合物合成橡胶外层。
- 应用: 中等压力液压管道 (液压油、防冻剂、空气和水), 环保材料。
- 适配接头: 两件式编织类扣压接头
- EN 854 2TE
- 温度范围: -40°C~+100°C
- 空气: 最高+70°C

- Hose structure: one layer of high tensile fiber braid, oil-resistant synthetic rubber inner layer, abrasion, ozone, hydrocarbon resistant synthetic rubber outer layer.
- Application: medium pressure hydraulic pipeline (hydraulic oil, antifreeze, air and water), environmentally friendly material.
- Adapter: two-piece braided crimping connector
- EN 854 2TE
- Temperature range: -40°C~+100°C
- Air: up to +70

								#	
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code	
6	1/4	6	13.4	7.5	30	40	0.14	2TEHF-04	SH720004
8	5/16	8	14.9	6.8	27	50	0.15	2TEHF-05	SH720005
10	3/8	10	16.5	6.3	25	60	0.19	2TEHF-06	SH720006
12	1/2	13	19.7	5.8	23	70	0.24	2TEHF-08	SH720008
16	5/8	16	23.9	5.0	20	90	0.29	2TEHF-10	SH720010
20	3/4	19	27.0	4.5	18	110	0.41	2TEHF-12	SH720012
25	1	25	34.4	4.0	16	150	0.60	2TEHF-16	SH720016