

PTFE3 铁氟龙管-内层螺纹型系列-超柔软型

Teflon Tube -Inner thread series-Super soft type



■ 软管结构:特殊缠绕包扎PTFE 波纹管内层, SS304不锈钢钢丝编织层外层。

■ Hose structure: special wrapped PTFE corrugated tube inner layer, SS304 stainless steel wire braided outer layer.

■ 温度范围: -54°C~+204°C

■ Temperature range: -54°C~+204°C

							#	
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
10	3/8	9.5	13.7	6.9	28	25	PTFE3 9806	SH9806
12	1/2	12.7	20.8	8.6	35	38	PTFE3 9808	SH9808
16	5/8	15.9	23.1	9.7	39	50	PTFE3 9810	SH9810
20	3/4	19.1	27.2	7.6	30	63	PTFE3 9812	SH9812
25	1	25.4	34.0	6.9	28	76	PTFE3 9816	SH9816
32	1 1/4	31.8	39.9	6.9	28	88	PTFE3 9820	SH9820
40	1 1/2	38.1	46.0	5.2	21	114	PTFE3 9824	SH9824
50	2	50.8	58.9	3.4	14	133	PTFE3 9832	SH9832