



M3K-液压软管  
Hydraulic hose

- 软管结构:一/二层高强度钢丝编织层,耐油丁腈橡胶内层,耐天候耐油耐磨黑色合成橡胶外层。
- 应用:高压液压油路。
- 适配接头:一体式或两件式,编织类扣压接头
- SAE 100R17
- 温度范围:-40℃~+100℃

- Hose structure: one or two layers of high-strength steel wire braid, oil-resistant nitrile rubber inner layer, weather-resistant, oil-resistant and wear-resistant black synthetic rubber outer layer.
- Application: high-pressure hydraulic oil circuit.
- Adapter: one-piece or two-piece, braided crimping connector
- SAE 100R17
- Temperature range: -40℃~+100℃

|  |  |  |  |  |  |  |  | #          |                      |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------|----------------------|
| 公称内径<br>DN                                                                        | 软管内径<br>in                                                                        | 软管外径<br>mm                                                                        | 软管外径<br>mm                                                                        | 最大工作压力<br>MPa                                                                     | 爆破压力<br>MPa                                                                       | 最小弯曲半径<br>mm                                                                       | 重量<br>kg/m                                                                          | 型号<br>Type | 产品编码<br>Product Code |
| 5                                                                                 | 3/16                                                                              | 4.8                                                                               | 10.8                                                                              | 22.5                                                                              | 90                                                                                | 33                                                                                 |                                                                                     | M3K-03     | HH110303             |
| 6                                                                                 | 1/4                                                                               | 6.3                                                                               | 12.2                                                                              | 22.5                                                                              | 90                                                                                | 38                                                                                 |                                                                                     | M3K-04     | HH110304             |
| 8                                                                                 | 5/16                                                                              | 7.9                                                                               | 15.1                                                                              | 21.5                                                                              | 90                                                                                | 46                                                                                 |                                                                                     | M3K-05     | HH110305             |
| 10                                                                                | 3/8                                                                               | 9.5                                                                               | 16.0                                                                              | 22.5                                                                              | 90                                                                                | 51                                                                                 |                                                                                     | M3K-06     | HH110306             |
| 12                                                                                | 1/2                                                                               | 12.5                                                                              | 20.2                                                                              | 22.5                                                                              | 90                                                                                | 71                                                                                 |                                                                                     | M3K-08     | HH110308             |
| 16                                                                                | 5/8                                                                               | 15.9                                                                              | 25.2                                                                              | 22.5                                                                              | 90                                                                                | 76                                                                                 |                                                                                     | M3K-10     | HH110310             |
| 20                                                                                | 3/4                                                                               | 19.1                                                                              | 29.1                                                                              | 22.5                                                                              | 90                                                                                | 97                                                                                 |                                                                                     | M3K-12     | HH110312             |
| 25                                                                                | 1                                                                                 | 25.4                                                                              | 37.6                                                                              | 22.5                                                                              | 90                                                                                | 114                                                                                |                                                                                     | M3K-16     | HH110316             |

注:公称内径6~12为一层高强钢丝编织,16~25为二层高强钢丝编织  
Note: Nominal inner diameter 6~12 is one layer of high-strength steel wire braiding, 16~25 is two layers of high-strength steel wire braiding



M4K-液压软管  
Hydraulic hose

- 软管结构:二层高强度钢丝编织层,耐油丁腈橡胶内层,耐天候耐油耐磨黑色合成橡胶外层。
- 应用:高压液压管路。
- 适配接头:一体式或两件式,编织类扣压接头
- SAE 100R19
- 温度范围:-40℃~+100℃

- Hose structure: two layers of high-strength steel wire braid, oil-resistant nitrile rubber inner layer, weather-resistant, oil-resistant and wear-resistant black synthetic rubber outer layer.
- Application: high-pressure hydraulic pipeline.
- Adapter: one-piece or two-piece, braided crimping connector
- SAE 100R19
- Temperature range: -40℃~+100℃

|  |  |  |  |  |  |  |  | #          |                      |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|------------|----------------------|
| 公称内径<br>DN                                                                          | 软管内径<br>in                                                                          | 软管外径<br>mm                                                                          | 软管外径<br>mm                                                                          | 最大工作压力<br>MPa                                                                       | 爆破压力<br>MPa                                                                         | 最小弯曲半径<br>mm                                                                         | 重量<br>kg/m                                                                            | 型号<br>Type | 产品编码<br>Product Code |
| 6                                                                                   | 1/4                                                                                 | 6.3                                                                                 | 12.2                                                                                | 28.0                                                                                | 110                                                                                 | 38                                                                                   |                                                                                       | M4K-04     | HH120404             |
| 8                                                                                   | 5/16                                                                                | 7.9                                                                                 | 15.1                                                                                | 28.0                                                                                | 110                                                                                 | 46                                                                                   |                                                                                       | M4K-05     | HH120405             |
| 10                                                                                  | 3/8                                                                                 | 9.5                                                                                 | 16.0                                                                                | 28.0                                                                                | 110                                                                                 | 51                                                                                   |                                                                                       | M4K-06     | HH120406             |
| 12                                                                                  | 1/2                                                                                 | 12.5                                                                                | 20.2                                                                                | 28.0                                                                                | 110                                                                                 | 71                                                                                   |                                                                                       | M4K-08     | HH120408             |
| 16                                                                                  | 5/8                                                                                 | 15.9                                                                                | 25.2                                                                                | 28.0                                                                                | 110                                                                                 | 76                                                                                   |                                                                                       | M4K-10     | HH120410             |
| 20                                                                                  | 3/4                                                                                 | 19.1                                                                                | 29.1                                                                                | 28.0                                                                                | 110                                                                                 | 97                                                                                   |                                                                                       | M4K-12     | HH120412             |
| 25                                                                                  | 1                                                                                   | 25.4                                                                                | 37.6                                                                                | 28.0                                                                                | 110                                                                                 | 114                                                                                  |                                                                                       | M4K-165    | HH120416             |