


AT3K-MINETUFF-液压软管

Hydraulic hose



- 软管结构: 一/二层高抗拉钢丝编织层或四层高抗拉钢丝缠绕层, 耐油合成橡胶内层, 耐磨损、臭氧、碳氢化合物, 合成橡胶。
- 应用: 高压液压管道 (液压油、防冻剂、空气和水)
- 适配接头: 一体式或两件式, 编织类扣压接头
- SAE 100R17, ISO 11237, EN 857 2SC
- 温度范围: -40°C~+100°C (钢丝编织)
- -40°C~+121°C (钢丝缠绕)

- Hose structure: one/two layers of high-tensile steel wire braid or four layers of high-tensile steel wire spiral, oil-resistant synthetic rubber inner layer, resistant to abrasion, ozone, hydrocarbons, synthetic rubber.
- Application: high-pressure hydraulic pipeline (hydraulic oil, antifreeze, air and water)
- Adapter: one-piece or two-piece, braided crimping connector
- SAE 100R17, ISO 11237, EN 857 2SC
- Temperature range: -40°C~+100°C (steel wire braid)
- -40°C~+121°C (steel wire spiral)

								#	
公称内径 DN	软管内径 in	软管外径 mm	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
6	1/4	6	12.1	22.5	90	50	0.17	AT3K-04	HH010204
8	5/16	8	14.1	21.5	86	55	0.19	AT3K-05	HH010205
10	3/8	10	15.6	21.0	84	65	0.26	AT3K-06	HH010206
12	1/2	13		21.0	84	90	0.36	AT3K-08	HH010208
20	3/4	19	27.7	24.0	96	125	0.79	AT3K-12	HH010212
25	1	25	35.6	21.0	84	150	1.23	AT3K-16	HH010216
32	1 1/4	32	47.0	21.0	84	419	2.69	AT3K-20	HH010220

注: 公称内径6~12为一层高抗拉钢丝编织, 20、25为二层高抗拉钢丝编织, 32为四层高抗拉钢丝缠绕。
Note: Nominal inner diameters 6 to 12 are braided with one layer of high-tensile steel wire, 20 and 25 are braided with two layers of high-tensile steel wire, and 32 is wound with four layers of high-tensile steel wire.

AT4K-MINETUFF-液压软管

Hydraulic hose



- 软管结构: 二层高抗拉钢丝编织层或四层高抗拉钢丝缠绕层, 耐油合成橡胶内层, 耐磨损、臭氧、碳氢化合物, 合成橡胶。
- 应用: 高压液压管道 (液压油、防冻剂、空气和水)
- 适配接头: 一体式或两件式扣压接头
- SAE 100R19
- 温度范围: -40°C~+100°C (钢丝编织)
- -40°C~+121°C (钢丝缠绕)

- Hose structure: two layers of high-tensile steel wire braid or four layers of high-tensile steel wire spiral, oil-resistant synthetic rubber inner layer, resistant to abrasion, ozone, hydrocarbons, synthetic rubber.
- Application: high-pressure hydraulic pipeline (hydraulic oil, antifreeze, air and water)
- Adapter: one-piece or two-piece crimping connector
- SAE 100R19
- Temperature range: -40°C~+100°C (steel wire braid)
- -40°C~+121°C (steel wire spiral)

								#	
公称内径 DN	软管内径 in	软管外径 mm	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
16	5/8	16	23.7	28.0	112	101	0.60	AT4K2-10	HH020210
20	3/4	19	29.3	28.0	112	130	0.98	AT4K2-12	HH020212
10	3/8	10	20.3	28.0	112	64	0.61	AT4K2-06	HH040206
12	1/2	13	23.8	28.0	112	90	0.82	AT4K2-08	HH040208
16	5/8	16	27.4	28.0	112	100	1.10	AT4K2-10	HH040210
20	3/4	19	30.7	28.0	112	130	1.23	AT4K2-12	HH040212
25	1	25	38.0	28.0	112	150	1.80	AT4K2-16	HH040216
32	1 1/4	32	47.5	28.0	112	230	2.47	AT4K2-20	HH040220
40	1 1/2	38	53.5	29.0	116	560	3.27	AT4K2-24	HH040224
50	2	51	68.1	28.0	112	590	4.67	AT4K2-32	HH040232

注: AT4K2-10、AT4K2-12为二层高抗拉钢丝编织, 其余为四层高抗拉钢丝缠绕。
Note: AT4K2-10 and AT4K2-12 are two-layer high-tensile steel wire braids, and the others are four-layer high-tensile steel wire windings.