



GH663-液压软管

Hydraulic hose

- 软管结构：一层钢丝编织增强层，合成橡胶内层，高耐磨合成橡胶外层
- 应用：石油基或水基液压油的液压系统，适用各种工业行业。
- 适配接头：一体式或两件式，编织类扣压接头
- SAE 100R1AT Type S, EN853 1SN, ISO 1436-1 Type 1SH
- 温度范围：-46°C~+127°C
- Hose structure: one steel wire braided reinforcement layer, synthetic rubber inner layer, high wear-resistant synthetic rubber outer layer
- Application: hydraulic system with petroleum-based or water-based hydraulic oil, suitable for various industrial industries.
- Adapter: one-piece or two-piece, braided crimping connector
- SAE 100R1AT Type S, EN853 1SN, ISO 1436-1 Type 1SH
- Temperature range: -46°C~+127°C

							#	型号 Type	产品编码 Product Code
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m			
6	1/4	6.4	13.5	25.5	102.0	51	0.24	GH663-04	HH066304
8	5/16	7.9	15.7	22.5	90.0	58	0.27	GH663-05	HH066305
10	3/8	9.7	17.5	23.5	94.0	62.5	0.37	GH663-06	HH066306
12	1/2	12.7	20.6	20.0	80.0	90	0.45	GH663-08	HH066308
16	5/8	15.9	24.5	14.0	56.0	103	0.52	GH663-10	HH066310
20	3/4	19.1	27.8	13.8	55.2	120	0.67	GH663-12	HH066312
25	1	25.4	35.8	10.3	41.2	150	1.01	GH663-16	HH066316
32	1 1/4	31.8	43.4	6.9	27.6	210	1.31	GH663-20	HH066320
40	1 1/2	38.1	50.6	5.2	20.8	250	1.56	GH663-24	HH066324
50	2	50.8	64.0	4.1	16.4	315	1.95	GH663-32	HH066332



GH781-液压软管

Hydraulic hose

- 软管结构：二层钢丝编织增强层，合成橡胶内层，高耐磨合成橡胶外层
- 应用：石油基或水基液压油的液压系统，适用各种工业行业。
- 适配接头：一体式或两件式，编织类扣压接头
- SAE 100R2AT Type S, EN853 2SN
- 温度范围：-46°C~+127°C
- Hose structure: two layers of steel wire braided reinforcement, synthetic rubber inner layer, high wear-resistant synthetic rubber outer layer
- Application: hydraulic systems with petroleum-based or water-based hydraulic oil, suitable for various industrial industries.
- Adapter: one-piece or two-piece, braided crimping connector
- SAE 100R2AT Type S, EN853 2SN
- Temperature range: -46°C~+127°C

							#	型号 Type	产品编码 Product Code
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m			
6	1/4	6.4	13.5	44.8	179.2	50.8	0.33	GH781-04	HH078104
8	5/16	7.9	15.7	35.0	140.0	55	0.36	GH781-05	HH078105
10	3/8	9.7	17.5	36.6	146.4	63.5	0.40	GH781-06	HH078106
12	1/2	12.7		31.0	124.0	88.9	0.58	GH781-08	HH078108
16	5/8	15.9	23.6	27.6	110.4	101.6	0.65	GH781-10	HH078110
20	3/4	19.1	27.9	24.1	96.4	120.7	0.79	GH781-12	HH078112
25	1	25.4	36.1	20.7	82.8	152.4	1.07	GH781-16	HH078116
32	1 1/4	31.8	41.9	17.2	68.8	209.6	1.62	GH781-20	HH078120
40	1 1/2	38.1	51.6	13.8	55.2	254	2.08	GH781-24	HH078124
50	2	50.8	64.3	11.0	44.0	317.5	2.83	GH781-32	HH078132