



EC110L-液压软管

Hydraulic hose

- 软管结构: 一层钢丝编织增强层, 合成橡胶内层, 黑色合成橡胶外层。
 - 应用: 石油基或水基液压油的液压系统, 适用各种工业行业。
 - SAE 100R1AT Type S, EN853 1SN
 - 温度范围: -40°C~+100°C。
 - 适配接头: 一体式或两件式, 编织类扣压接头。
- Hose structure: one steel wire braided reinforcement layer, synthetic rubber inner layer, black synthetic rubber outer layer
 - Application: hydraulic system with petroleum-based or water-based hydraulic oil, suitable for various industrial industries.
 - SAE 100R1AT Type S, EN853 1SN
 - Temperature range: -40°C~+100°C
 - Adapter: one-piece or two-piece, braided crimping connector

								#	
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code	
6	1/4	6.4	13.2	22.5	90.2	100	0.22	EC110-04L	HH011004
8	5/16	7.9	14.8	21.5	86.0	115	0.26	EC110-05L	HH011005
10	3/8	9.5	17.2	18.0	72.0	130	0.33	EC110-06L	HH011006
12	1/2	12.7	20.4	16.0	64.0	180	0.41	EC110-08L	HH011008
16	5/8	15.9	23.5	13.0	52.0	200	0.47	EC110-10L	HH011010
20	3/4	19.0	27.5	10.5	42.0	240	0.59	EC110-12L	HH011012
25	1	25.4	35.4	8.8	35.2	300	0.87	EC110-16L	HH011016
32	1 1/4	31.8	43.5	6.3	25.2	420	1.20	EC110-20L	HH011020
40	1 1/2	38.1	50.0	5.0	20.0	500	1.40	EC110-24L	HH011024
50	2	50.8	63.6	4.0	16.0	630	1.90	EC110-32L	HH011032



EC210L-液压软管

Hydraulic hose

- 软管结构: 二层钢丝编织增强层, 合成橡胶内层, 黑色合成橡胶外层。
 - 应用: 石油基或水基液压油的液压系统, 适用各种工业行业。
 - SAE 100R2AT Type S, EN853 2SN
 - 温度范围: -40°C~+100°C
 - 适配接头: 一体式或两件式, 编织类扣压接头
- Hose structure: one steel wire braided reinforcement layer, synthetic rubber inner layer, black synthetic rubber outer layer
 - Application: hydraulic system with petroleum-based or water-based hydraulic oil, suitable for various industrial industries.
 - SAE 100R1AT Type S, EN853 1SN
 - Temperature range: -40°C~+100°C
 - Adapter: one-piece or two-piece, braided crimping connector

								#	
公称内径 DN	软管内径 in	软管外径 mm	mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
6	1/4	6.4	15.0	40.0	160.0	100	0.38	EC210-04L	HH021004
8	5/16	7.9	16.5	35.0	140.0	115	0.43	EC210-05L	HH021005
10	3/8	9.5	18.9	33.0	132.0	130	0.54	EC210-06L	HH021006
12	1/2	12.7	22.2	27.5	110.0	180	0.64	EC210-08L	HH021008
16	5/8	15.9	25.2	25.0	100.0	200	0.75	EC210-10L	HH021010
20	3/4	19.0	29.2	21.5	86.0	240	0.93	EC210-12L	HH021012
25	1	25.4	37.2	16.5	66.2	300	1.29	EC210-16L	HH021016
32	1 1/4	31.8	47.3	12.5	50.2	420	1.86	EC210-20L	HH021020
40	1 1/2	38.1	53.7	9.0	36.0	500	2.10	EC210-24L	HH021024
50	2	50.8	66.7	8.0	32.0	630	2.76	EC210-32L	HH021032