

431-不剥胶高压液压软管

Non-peeling high pressure hydraulic hose



- 软管结构: 二层高强度钢丝编织增强层, 间隔橡胶层, 合成橡胶内层, 耐油耐磨耐天候黑色合成橡胶外层。
- 应用: 高压状况, 用于石油基液压油, 水乙二醇, 乳化液, 热油, 油脂, 润滑剂, 原油和燃油, 空气, 水。用于17bar以上压力气体时需针刺。
- 适配接头: 派克不剥胶一体式接头
- SAE 100 R16
- 适配接头: 扣压式43系列
- 温度范围: -40°C~+125°C
- 空气: 最高+70°C, 水: 最高+85°C

- Hose structure: two layers of high-strength steel wire braided reinforcement layer, interval rubber layer, synthetic rubber inner layer, oil-resistant, wear-resistant and weather-resistant black synthetic rubber outer layer.
- Application: high-pressure conditions, used for petroleum-based hydraulic oil, water glycol, emulsion, hot oil, grease, lubricant, crude oil and fuel oil, air, water. Needle puncture is required for pressure gas above 17 bar.
- Adapter: Parker non-peeling one-piece connector
- SAE 100 R16
- Adapter: Crimp type 43 series
- Temperature range: -40°C~+125°C
- Air: up to +70°C, water: up to +85°C

							#		
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code	
6	1/4	6.3	13.0	34.5	138.0	50	0.27	431-04	HH043104
8	5/16	7.9	15.0	29.3	117.0	55	0.36	431-05	HH043105
10	3/8	9.5	17.0	27.5	110.0	65	0.42	431-06	HH043106
12	1/2	12.7	20.0	24.0	96.0	90	0.51	431-08	HH043108
16	5/8	15.9	24.0	19.0	76.0	100	0.66	431-10	HH043110
20	3/4	19.1	28.0	15.5	62	120	0.80	431-12	HH043112
25	1	25.4	36.0	13.8	55	150	1.22	431-16	HH043116

372-不剥胶高压液压软管

Non-peeling high pressure hydraulic hose



- 软管结构: 三层高强度钢丝编织增强层, 合成橡胶内层, 耐油耐磨耐天候黑色合成橡胶外层。
- 应用: 高压状况, 用于石油基液压油, 水乙二醇, 乳化液, 热油, 油脂, 润滑剂, 原油和燃油, 空气, 水。用于17bar以上压力气体时需针刺。
- 适配接头: 派克不剥胶一体式接头
- 工作压力: 4SP压力等级
- 适配接头: 扣压式70系列
- 温度范围: -40°C~+100°C
- 空气: 最高+70°C, 水: 最高+85°C

- Hose structure: three layers of high-strength steel wire braided reinforcement layer, synthetic rubber inner layer, oil-resistant, wear-resistant and weather-resistant black synthetic rubber outer layer.
- Application: high-pressure conditions, for petroleum-based hydraulic oil, water glycol, emulsion, hot oil, grease, lubricant, crude oil and fuel oil, air, water. Needle puncture is required for pressure gas above 17 bar.
- Adapter: Parker non-peeling one-piece connector
- Working pressure: 4SP pressure level
- Adapter: Crimp type 70 series
- Temperature range: -40°C~+100°C
- Air: up to +70°C, water: up to +85°C

							#		
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code	
10	3/8	9.5	21.4	44.5	178.0	120	0.73	372-06	HH037206
12	1/2	12.7	24.6	41.5	166.0	160	0.90	372-08	HH037208
16	5/8	15.9	28.2	35.0	140.0	210	1.09	372-10	HH037210
20	3/4	19.1	32.2	35.0	140.0	260	1.36	372-12	HH037212
25	1	25.4	39.7	28.0	112.0	310	1.78	372-16	HH037216