

M5K-液压软管

Hydraulic hose



- 软管结构: 二层高强度钢丝编织层, 耐油丁腈橡胶内层, 耐候耐油耐磨黑色合成橡胶外层。
- 应用: 高压液压油路。
- 适配接头: 一体式或两件式, 编织类扣压接头
- 温度范围: -40°C~+100°C

- Hose structure: two layers of high-strength steel wire braid, oil-resistant nitrile rubber inner layer, weather-resistant, oil-resistant and wear-resistant black synthetic rubber outer layer.
- Application: high-pressure hydraulic oil circuit.
- Adapter: one-piece or two-piece, braided crimping connector
- Temperature range: -40°C~+100°C

								#	
公称内径 DN	软管内径 in	软管外径 mm	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
6	1/4	6.4	13.7	34.5	137.9	51		M5K-04	HH120504
8	5/16	7.9	15.5	34.5	137.9	56		M5K-05	HH120505
10	3/8	9.5	17.5	34.5	137.9	64		M5K-06	HH120506
12	1/2	12.7	21.8	34.5	137.9	89		M5K-08	HH120508

EFG4K-液压软管

Hydraulic hose



- 软管结构: 四层高强度钢丝缠绕层, 耐油丁腈橡胶内层, 耐油耐磨黑色合成橡胶外层。
- 应用: 高压液压管路。
- 适配接头: 一体式或两件式扣压接头
- SAE 100R12
- 温度范围: -40°C~+121°C

- Hose structure: Four layers of high-strength steel wire winding, oil-resistant nitrile rubber inner layer, oil-resistant and wear-resistant black synthetic rubber outer layer.
- Application: High-pressure hydraulic pipeline.
- Adapter: One-piece or two-piece crimping connector
- SAE 100R12
- Temperature range: -40°C~+121°C

								#	
公称内径 DN	软管内径 in	软管外径 mm	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
10	3/8	9.5	20.3	27.6	110	64		EFG4K-06	HH140406
12	1/2	12.7	24.1	27.6	110	89		EFG4K-08	HH140408
16	5/8	15.9	27.7	27.6	110	102		EFG4K-10	HH140410
20	3/4	19.1	30.7	27.6	110	122		EFG4K-12	HH140412
25	1	25.4	38.1	27.6	110	152		EFG4K-16	HH140416
32	1 1/4	31.8	47.0	27.6	110	211		EFG4K-20	HH140420
76	3	76.2	98.0	27.6	110	890		EFG4K-48	HH140448