



40BAR-REFITTEX低压管

Low pressure pipe

- 软管结构: 一层纤维编织增强层, 软聚氯乙烯内外层。
- 应用: 压缩空气、水、杀菌剂溶液、杀虫剂和肥料。
- 温度范围: -10°C~+50°C

- Hose structure: one fiber braided reinforcement layer, soft PVC inner and outer layers.
- Application: compressed air, water, fungicide solution, pesticide and fertilizer.
- Temperature range: -10°C~+50°C

							#	
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
6	1/4	6	12	4.0	12.0	0.11	FITT40-04	SH004004
8	5/16	8	14	4.0	12.0	0.13	FITT40-05	SH004005
10	3/8	10	16	4.0	12.0	0.16	FITT40-06	SH004006
12	1/2	13	21	4.0	12.0	0.27	FITT40-08	SH004008
16	5/8	16	24	4.0	12.0	0.31	FITT40-10	SH004010
20	3/4	19	28	4.0	12.0	0.41	FITT40-12	SH004012
25	1	25	35	4.0	12.0	0.61	FITT40-16	SH004016



80BAR-REFITTEX低压管

Low pressure pipe

- 软管结构: 两层纤维编织增强层, 软聚氯乙烯内外层。
- 应用: 压缩空气、水、杀菌剂溶液、杀虫剂和肥料。
- 温度范围: -10°C~+50°C

- Hose structure: two layers of fiber braided reinforcement, soft PVC inner and outer layers.
- Application: compressed air, water, fungicide solution, pesticide and fertilizer
- Temperature range: -10°C~+50°C

							#	
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
8	5/16	8	15	8.0	24.0	0.16	FITT80-05	SH008005
10	3/8	10	18	8.0	24.0	0.22	FITT80-06	SH008006
12	1/2	13	23	8.0	24.0	0.36	FITT80-08	SH008008
16	5/8	16	26	8.0	24.0	0.42	FITT80-10	SH008010
20	3/4	19	30	8.0	24.0	0.53	FITT80-12	SH008012