



540N-树脂管

Resin tube

- 软管结构: 一层高抗拉纤维加强层, 尼龙内层, 聚氨酯黑色外层
- 应用: 液压和气动系统。良好的化学相容性, 工作温度范围宽, 可用于农业喷洒、聚氨酯泡沫搅拌机、机器人、消防液体和热水。
- 适配接头: 派克不剥胶一体式接头
- SAE 100R7
- 温度范围: -40°C~+100°C

- Hose structure: one layer of high tensile fiber reinforcement, nylon inner layer, polyurethane black outer layer
- Application: hydraulic and pneumatic systems. Good chemical compatibility, wide operating temperature range, can be used for agricultural spraying, polyurethane foam mixers, robots, firefighting fluids and hot water.
- Adapter: Parker non-peeling one-piece connector
- SAE 100R7
- Temperature range: -40°C~+100°C

							#	产品编码	
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	Product Code	
3	1/8	3	9	20.7	83	13	0.05	540N-02	SH054002
5	3/16	5	11	20.7	83	19	0.06	540N-03	SH054003
6	1/4	6	13	19.0	76	38	0.09	540N-04	SH054004
8	5/16	8	14	17.2	69	44	0.10	540N-05	SH054005
10	3/8	10	16	15.5	62	51	0.13	540N-06	SH054006
12	1/2	13	21	13.8	55	76	0.19	540N-08	SH054008
20	3/4	19	27	8.6	34	152	0.25	540N-12	SH054012



2245N-料管

Material pipe

- 软管结构: 两层高强度钢丝缠绕层, 一层编织钢丝层, 聚酰胺材料内层, 黑色聚氨酯于10及以上聚酰胺材料外层。
- 应用: 由于聚酰胺芯管优良的耐化学性和耐高压性能, 适用于一般工业和移动液压应用以及气体提供高压服务和各种各样的流体
- 适配接头: 派克不剥胶一体式接头
- SAE 100R9
- 温度范围: -40°C~+100°C

- Hose structure: two layers of high-strength steel wire winding, one layer of braided steel wire, inner layer of polyamide material, black polyurethane and outer layer of polyamide material 10 and above.
- Application: Due to the excellent chemical resistance and high pressure resistance of the polyamide core tube, it is suitable for general industrial and mobile hydraulic applications and gas to provide high-pressure services and a variety of fluids
- Adapter: Parker non-peeling one-piece connector
- SAE 100R9
- Temperature range: -40°C~+100°C

							#	产品编码
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	Product Code
6	1/4	6.3	12.5	45.0	180	70	2245N-04	SH224504
8	5/16	8.2	14.3	40.0	160	100	2245N-05	SH224505
10	3/8	9.7	17.0	37.5	150	120	2245N-06	SH224506
12	1/2	12.8	20.7	35.0	140	165	2245N-08	SH224508
16	5/8	16	24.5	33.0	132	200	2245N-10	SH224510
20	3/4	19.6	28.5	30.0	120	240	2245N-12	SH224512
25	1	25.0	34.0	27.5	110	280	2245N-16	SH224516