



301-不剥胶高压液压软管

Non-peeling high pressure hydraulic hose

- 软管结构: 二层高强度钢丝编织增强层, 合成橡胶内层, MSHA认可橡胶外层。
- 应用: 用于石油基液压油, 润滑油, 水, 水乙二醇, 乳液和空气。用于17bar以上压力气体时需针刺。
- 适配接头: 派克不剥胶一体式接头
- SAE 100 R2 AT
- 适配接头: 43系列
- 温度范围: -40°C~+125°C
- 空气: 最高+70°C, 水: 最高+85°C

- Hose structure: two layers of high-strength steel wire braided reinforcement, synthetic rubber inner layer, MSHA approved rubber outer layer.
- Application: for petroleum-based hydraulic oil, lubricating oil, water, water glycol, emulsion and air. Needle puncture is required for pressure gas above 17 bar.
- Adapter: Parker non-peeling one-piece connector
- SAE 100 R2 AT
- Adapter: 43 series
- Temperature range: -40°C~+125°C
- Air: up to +70°C, water: up to +85

								#	
公称内径 DN	软管内径 in	软管外径 mm	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
5	3/16	4.8	14.0	34.5	138.0	90	0.31	301-03	HH030103
6	1/4	6.3	15.0	34.5	138.0	100	0.39	301-04	HH030104
10	3/8	9.5	19.0	27.5	110.0	130	0.55	301-06	HH030106
12	1/2	12.7	22.0	24.0	96.0	180	0.67	301-08	HH030108
16	5/8	15.9	25.0	19.0	76.0	200	0.77	301-10	HH030110
20	3/4	19.1	30.0	15.5	62.0	240	1.00	301-12	HH030112
25	1	25.4	38.0	13.8	55.0	300	1.49	301-16	HH030116
32	1 1/4	31.5	48.0	11.2	45.0	420	1.73	301-20	HH030120
40	1 1/2	38.0	54.0	8.6	35.0	500	2.14	301-24	HH030124
50	2	51.0	68.0	7.8	31.0	630	2.96	301-32	HH030132



381-不剥胶高压液压软管

Non-peeling high pressure hydraulic hose

- 软管结构: 二层高强度钢丝编织增强层中间隔橡胶层, 丁腈橡胶内层, 具有良好的化学兼容性, 耐油耐磨耐候黑色合成橡胶外层。
- 应用: 高压状况, 用于石油基液压油, 水乙二醇, 乳液, 热油, 油脂, 润滑油, 原油和燃油, 空气, 水和生物油, 用于17bar以上压力气体时需针刺。
- 适配接头: 派克不剥胶一体式接头
- SAE 100 R2 AT, EN 853-2SN
- 适配接头: 扣压式43、71系列
- 温度范围: -40°C~+100°C
- 空气: 最高+70°C, 水: 最高+85°C

- Hose structure: Two layers of high-strength steel wire braided reinforcement layer with a rubber layer in the middle, nitrile rubber inner layer, good chemical compatibility, oil-resistant, wear-resistant and weather-resistant black synthetic rubber outer layer.
- Application: High-pressure conditions, used for petroleum-based hydraulic oil, water glycol, emulsion, hot oil, grease, lubricant, crude oil and fuel oil, air, water and bio-oil, need to be punctured when used for pressure gas above 17 bar.
- Adapter: Parker non-peeling one-piece connector
- SAE 100 R2 AT, EN 853-2SN
- Adapter: Crimp type 43, 71 series
- Temperature range: -40°C~+100°C
- Air: up to +70°C, water: up to +85°C

								#	
公称内径 DN	软管内径 in	软管外径 mm	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
6	1/4	6.3	15.0	40.0	160.0	100	0.39	381-04	HH038104
8	5/16	7.9	16.6	36.0	144.0	115	0.42	381-05	HH038105
10	3/8	9.5	19.0	35.0	140.0	130	0.55	381-06	HH038106
12	1/2	12.7	22.2	29.7	118.0	180	0.67	381-08	HH038108
16	5/8	15.9	25.4	25.0	100.0	200	0.77	381-10	HH038110
20	3/4	19.1	39.3	21.5	86.0	240	1.00	381-12	HH038112
25	1	25.4	37.8	17.5	70.0	300	1.49	381-16	HH038116
32	1 1/4	31.8	47.5	15.7	62.0	420	1.73	381-20	HH038120
40	1 1/2	38.1	55.0	12.5	50.0	500	2.14	381-24	HH038124
50	2	50.8	67.0	9.0	36.0	630	2.96	381-32	HH038132