



GH506-液压软管

Hydraulic hose

- 软管结构: 一层钢丝编织增强层, 合成橡胶内层, 高耐磨合成橡胶外层
- 应用: 石油基或水基液压油的液压系统, 适用各种工业行业。
- 适配接头: 一体式或两件式, 编织类扣压接头
- SAE 100R1AT Type S, EN853 1SN, ISO 1436-1Type 1SH
- 温度范围: -46°C~+127°C
- Hose structure: one steel wire braided reinforcement layer, synthetic rubber inner layer, high wear-resistant synthetic rubber outer layer
- Application: hydraulic system with petroleum-based or water-based hydraulic oil, suitable for various industrial industries.
- Adapter: one-piece or two-piece, braided crimping connector
- SAE 100R1AT Type S, EN853 1SN, ISO 1436-1Type 1SH
- Temperature range: -46°C~+127°C

								#	
公称内径 DN	软管内径 in	软管外径 mm	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
20	3/4	19.1	32.3	42.0	168.0	280	1.49	GH506-12	HH050612
25	1	25.4	38.4	38.0	152.0	340	2.05	GH506-16	HH050616
32	1 1/4	31.8	45.5	35.0	140.0	460	2.54	GH506-20	HH050620
40	1 1/2	38.1		30.0	120.0	560	3.27	GH506-24	HH050624
50	2	50.8	68.1	25.0	100.0	700	4.58	GH506-32	HH050632



FC273-液压软管

Hydraulic hose

- 软管结构: 四或六层高负荷钢丝缠绕层 (-12、-16为四层, -20、-24、-32为六层), 合成橡胶内层, 高耐磨合成橡胶外层
- 应用: 石油基或水基液压油的液压系统, 适用各种工业行业。
- 适配接头: 两件式扣压接头, 六层钢丝管需内外剥胶
- EN856 4SH, EN 856 R13, ISO 3862 R13
- 温度范围: -40°C~+121°C
- Hose structure: four or six layers of high-load steel wire winding (-12, -16 are four layers, -20, -24, -32 are six layers), synthetic rubber inner layer, high wear-resistant synthetic rubber outer layer
- Application: hydraulic system with petroleum-based or water-based hydraulic oil, suitable for various industrial industries.
- Adapter: two-piece crimping connector, six-layer steel wire tube needs to be stripped inside and outside
- EN856 4SH, EN 856 R13, ISO 3862 R13
- Temperature range: -40°C~+121°C

								#	
公称内径 DN	软管内径 in	软管外径 mm	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
20	3/4	19.1	32.0	35.0	140.0	240	1.56	FC273-12	HH027312
25	1	25.4	38.6	35.0	140.0	300	1.96	FC273-16	HH027316
32	1 1/4	31.8	49.8	35.0	140.0	420	3.66	FC273-20	HH027320
40	1 1/2	38.1	57.4	35.0	140.0	500	4.70	FC273-24	HH027324
50	2	50.8	71.1	35.0	140.0	640	7.11	FC273-32	HH027332