

20BAR-REFITTEX低压管

Low pressure pipe



- 软管结构: 一层纤维编织增强层, 软聚氯乙烯内外层。
- 应用: 压缩空气、水、杀菌剂溶液、杀虫剂和肥料。
- 温度范围: -10°C~+50°C

- Hose structure: one fiber braided reinforcement layer, soft PVC inner and outer layers.
- Application: compressed air, water, fungicide solution, pesticide and fertilizer.
- Temperature range: -10°C~+50°C

							#	
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
6	1/4	6	11	2.0	6.0	0.09	FITT20-04	SH002004
8	5/16	8	13	2.0	6.0	0.10	FITT20-05	SH002005
10	3/8	10	15	2.0	6.0	0.13	FITT20-06	SH002006
12	1/2	13	19	2.0	6.0	0.19	FITT20-08	SH002008
16	5/8	16	23	2.0	6.0	0.27	FITT20-10	SH002010
20	3/4	19	26	2.0	6.0	0.31	FITT20-12	SH002012
25	1	25	33	2.0	6.0	0.46	FITT20-16	SH002016

20BAR-C-REFITTEX低压管

Low pressure pipe



- 软管结构: 一层纤维编织增强层, 软聚氯乙烯内外层。外层有蓝、红、黑、绿颜色
- 应用: 压缩空气、水和杀菌剂溶液。
- 温度范围: -10°C~+50°C

- Hose structure: one fiber braided reinforcement layer, soft PVC inner and outer layers. The outer layer is available in blue, red, black and green colors.
- Application: compressed air, water and bactericide solution.
- Temperature range: -10°C~+50°C

							#	
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code
6	1/4	6	11	2.0	6.0	0.09	FITT20C-04	SH002104
8	5/16	8	13	2.0	6.0	0.11	FITT20C-05	SH002105
10	3/8	10	15	2.0	6.0	0.14	FITT20C-06	SH002106
12	1/2	13	19	2.0	6.0	0.21	FITT20C-08	SH002108
20	3/4	19	26	2.0	6.0	0.32	FITT20C-12	SH002112
25	1	25	33	2.0	6.0	0.47	FITT20C-16	SH002116

注: 外层颜色随机发送, 如需指定请备注说明。

Note: The outer color is sent randomly, please make a note if you need to specify.