

492-不剥胶高压液压软管

Non-peeling high pressure hydraulic hose



- 软管结构：一层高强度钢丝增强层，合成橡胶内层，耐油耐磨耐天候黑色合成橡胶外层。
- 应用：高压状况，用于石油基液压油，水乙二醇，乳化液，热油，油脂，润滑剂，原油和燃油，空气，水。用于17bar以上压力气体时需针刺。
- 适配接头：派克不剥胶一体式接头
- EN 857-1SC
- 适配接头：扣压式46系列
- 温度范围：-40°C~+100°C
- 空气：最高+70°C，水：最高+85°C

- Hose structure: one layer of high-strength steel wire reinforcement, synthetic rubber inner layer, oil-resistant, wear-resistant and weather-resistant black synthetic rubber outer layer.
- Application: High-pressure conditions, used for petroleum-based hydraulic oil, water glycol, emulsion, hot oil, grease, lubricant, crude oil and fuel, air, water. Needle puncture is required for pressure gas above 17 bar.
- Adapter: Parker non-peeling one-piece connector
- EN 857-1SC
- Adapter: Crimp type 46 series
- Temperature range: -40°C~+100°C
- Air: up to +70°C, water: up to +85°C

公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	#	型号 Type	产品编码 Product Code
6	1/4	6.3	11.5	28.0	112.0	75	0.18	492-04	HH049204
8	5/16	7.9	13.6	25.0	100.0	85	0.21	492-05	HH049205
10	3/8	9.5	15.5	22.5	90.0	90	0.25	492-06	HH049206
12	1/2	12.7	18.9	19.0	76.0	130	0.33	492-08	HH049208
16	5/8	15.9	22.2	15.0	60.0	150	0.41	492-10	HH049210
20	3/4	19.1	26.0	15.0	60.0	180	0.56	492-12	HH049212
25	1	25.4	33.3	11.0	44.0	230	0.75	492-16	HH049216
32	1 1/4	31.8	40.0	7.5	30.0	335	0.93	492-20	HH049220

462-不剥胶高压液压软管

Non-peeling high pressure hydraulic hose



- 软管结构：二层高强度钢丝编织增强层中间隔橡胶层，合成橡胶内层，耐油耐磨耐天候黑色合成橡胶外层。
- 应用：高压状况，用于石油基液压油，水乙二醇，乳化液，热油，油脂，润滑剂，原油和燃油，空气，水和生物油，用于17bar以上压力气体时需针刺
- 适配接头：派克不剥胶一体式接头
- EN 857-2SC
- 适配接头：46系列
- 温度范围：-40°C~+100°C
- 空气：最高+70°C，水：最高+85°C

- Hose structure: two layers of high-strength steel wire braided reinforcement layer with a rubber layer in the middle, synthetic rubber inner layer, oil-resistant, wear-resistant and weather-resistant black synthetic rubber outer layer.
- Application: high-pressure conditions, used for petroleum-based hydraulic oil, water glycol, emulsion, hot oil, grease, lubricant, crude oil and fuel oil, air, water and bio-oil, need to be needled when used for pressure gas above 17 bar
- Adapter: Parker non-peeling one-piece connector
- EN 857-2SC
- Adapter: 46 series
- Temperature range: -40°C~+100°C
- Air: up to +70°C, water: up to +85°C

公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	#	型号 Type	产品编码 Product Code
6	1/4	6.3	13.4	42.5	170.0	75	0.30	462-04	HH046204
8	5/16	7.9	15.0	40.0	160.0	85	0.35	462-05	HH046205
10	3/8	9.5	17.2	35.0	140.0	90	0.42	462-06	HH046206
12	1/2	12.7	20.4	31.0	124.0	130	0.52	462-08	HH046208
16	5/8	15.9	23.9	28.0	112.0	160	0.66	462-10	HH046210
20	3/4	19.1	27.7	28.0	112.0	195	0.86	462-12	HH046212
25	1	25.4	35.4	21.0	84.0	250	1.17	462-16	HH046216
32	1 1/4	31.8	43.0	17.2	68.8	335	1.50	462-20	HH046220