



471TC-液压软管

Hydraulic hose

- 软管结构: 二层高强度钢丝编织增强层, 耐油丁腈合成橡胶内层, 耐油耐磨耐候黑色合成橡胶外层。
- 应用: 石油基液压油和润滑油
- 适配接头: 派克不剥胶一体式接头
- EN 857-2SC
- 适配接头: 43系列
- 温度范围: -40°C~+100°C

- Hose structure: two layers of high-strength steel wire braided reinforcement, oil-resistant nitrile synthetic rubber inner layer, oil-resistant, wear-resistant and weather-resistant black synthetic rubber outer layer.
- Application: petroleum-based hydraulic oil and lubricating oil
- Adapter: Parker non-peeling one-piece connector
- EN 857-2SC
- Adapter: 43 series
- Temperature range: -40°C~+100°C

							#		
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code	
6	1/4	6.3	13.0	40.0	160.0	50	0.30	471TC-04	HH047104
8	5/16	7.9	15.0	36.0	144.0	55	0.35	471TC-05	HH047105
10	3/8	9.5	17.0	35.0	140.0	65	0.42	471TC-06	HH047106
12	1/2	12.7	20.0	29.7	119.0	90	0.52	471TC-08	HH047108
16	5/8	15.9	24.0	25.0	100.0	100	0.66	471TC-10	HH047110
20	3/4	19.1	28.0	21.5	86.0	120	0.86	471TC-12	HH047112
25	1	25.4	35.0	17.5	70.0	150	1.17	471TC-16	HH147116



472TC-不剥胶高压液压软管

Non-peeling high pressure hydraulic hose

- 软管结构: 二层高强度钢丝编织增强层, 耐油丁腈合成橡胶内层, 耐油耐磨耐候黑色合成橡胶外层。
- 应用: 石油基液压油和润滑油
- 适配接头: 派克不剥胶一体式接头
- ISO 11237-1, SAE 100R16
- 适配接头: 扣压式43系列
- 温度范围: -40°C~+100°C

- Hose structure: two layers of high-strength steel wire braided reinforcement layer, oil-resistant nitrile synthetic rubber inner layer, oil-resistant, wear-resistant and weather-resistant black synthetic rubber outer layer.
- Application: petroleum-based hydraulic oil and lubricating oil
- Adapter: Parker non-peeling one-piece connector
- ISO 11237-1, SAE 100R16
- Adapter: Crimp type 43 series
- Temperature range: -40°C~+100°C

							#		
公称内径 DN	软管内径 in	软管外径 mm	最大工作压力 MPa	爆破压力 MPa	最小弯曲半径 mm	重量 kg/m	型号 Type	产品编码 Product Code	
32	1 1/4	31.8	45.0	15.7	63.0	210	2.01	472TC-20	HH047220
40	1 1/2	38.1	51.0	12.5	50.0	250	2.16	472TC-24	HH047224
50	2	50.8	65.0	9.0	36.0	315	2.90	472TC-32	HH047232