



中压外螺纹转NPT外螺纹 Male Medium Pressure to Male NPT

P 中压-外	Px NPT	产品编号 Product No.	尺寸数据 in.(mm)			工作压力 Psig(bar)
			L	D	F (六角)	
1/4	1/8	-MNM-M04-MN2	1.37 (34.9)	0.11 (2.8)	0.50 (12.7)	15000 (1034)
1/4	1/4	-MNM-M04-MN4	1.56 (39.7)	0.11 (2.8)	0.56 (14.3)	15000 (1034)
1/4	3/8	-MNM-M04-MN6	1.63 (41.3)	0.11 (2.8)	0.69 (17.5)	15000 (1034)
1/4	1/2	-MNM-M04-MN8	1.87 (47.6)	0.11 (2.8)	0.87 (22.2)	15000 (1034)
3/8	1/8	-MNM-M06-MN2	1.56 (39.7)	0.19 (4.8)	0.63 (15.9)	15000 (1034)
3/8	1/4	-MNM-M06-MN4	1.75 (44.5)	0.20 (5.1)	0.63 (15.9)	15000 (1034)
3/8	3/8	-MNM-M06-MN6	1.75 (44.5)	0.20 (5.1)	0.69 (17.5)	15000 (1034)
3/8	1/2	-MNM-M06-MN8	2.00 (50.8)	0.20 (5.1)	0.87 (22.2)	15000 (1034)
9/16	1/4	-MNM-M09-MN4	2.06 (52.4)	0.25 (6.4)	0.94 (23.8)	15000 (1034)
9/16	3/8	-MNM-M09-MN6	2.06 (52.4)	0.31 (7.9)	0.94 (23.8)	15000 (1034)
9/16	1/2	-MNM-M09-MN8	2.25 (57.2)	0.31 (7.9)	0.94 (23.8)	15000 (1034)
9/16	3/4	-MNM-M09-MN12	2.31 (58.7)	0.31 (7.9)	1.06 (27.0)	10000 (690)
3/4	1/4	-MNM-M12-MN4	2.31 (58.7)	0.25 (6.4)	1.19 (30.2)	15000 (1034)
3/4	3/8	-MNM-M12-MN6	2.31 (58.7)	0.31 (7.9)	1.19 (30.2)	15000 (1034)
3/4	1/2	-MNM-M12-MN8	2.50 (63.5)	0.38 (9.6)	1.19 (30.2)	15000 (1034)
3/4	3/4	-MNM-M12-MN12	2.50 (63.5)	0.44 (11.1)	1.19 (30.2)	15000 (1034)
3/4	1	-MNM-M12-MN16	2.75 (69.9)	0.44 (11.1)	1.37 (34.9)	10000 (690)
1	1/4	-MNM-M16-MN4	2.81 (71.4)	0.25 (6.4)	1.50 (38.1)	15000 (1034)
1	3/8	-MNM-M16-MN6	2.81 (71.4)	0.31 (7.9)	1.50 (38.1)	15000 (1034)
1	1/2	-MNM-M16-MN8	3.06 (77.7)	0.38 (9.6)	1.50 (38.1)	15000 (1034)
1	3/4	-MNM-M16-MN12	3.06 (77.7)	0.56 (14.3)	1.50 (38.1)	10000 (690)
1	1	-MNM-M16-MN16	3.25 (82.6)	0.56 (14.3)	1.50 (38.1)	10000 (690)