



高压外螺纹转NPT外螺纹

Male High Pressure to Male NPT

P 高压外螺纹	Px NPT	产品编号 Product No.	尺寸数据 in.(mm)			工作压力 Psig(bar)
			L	D	F (六角)	
1/4	1/8	-HMM-H04-MN2	1.37 (34.9)	0.09 (2.3)	0.63 (15.9)	15000 (1034)
1/4	1/4	-HMM-H04-MN4	1.56 (39.7)	0.09 (2.3)	0.63 (15.9)	15000 (1034)
1/4	3/8	-HMM-H04-MN6	1.56 (39.7)	0.09 (2.3)	0.69 (17.5)	15000 (1034)
1/4	1/2	-HMM-H04-MN8	1.81 (46.0)	0.09 (2.3)	0.87 (22.2)	15000 (1034)
3/8	1/4	-HMM-H06-MN4	1.87 (47.6)	0.13 (3.2)	0.81 (20.6)	15000 (1034)
3/8	3/8	-HMM-H06-MN6	1.87 (47.6)	0.13 (3.2)	0.81 (20.6)	15000 (1034)
3/8	1/2	-HMM-H06-MN8	2.06 (52.4)	0.13 (3.2)	0.87 (22.2)	15000 (1034)
3/8	3/4	-HMM-H06-MN12	2.13 (54.0)	0.13 (3.2)	1.06 (27.0)	10000 (690)
9/16	1/4	-HMM-H09-MN4	2.13 (54.0)	0.19 (4.8)	1.19 (30.2)	15000 (1034)
9/16	3/8	-HMM-H09-MN6	2.13 (54.0)	0.19 (4.8)	1.19 (30.2)	15000 (1034)
9/16	1/2	-HMM-H09-MN8	2.37 (60.3)	0.19 (4.8)	1.19 (30.2)	15000 (1034)
9/16	3/4	-HMM-H09-MN12	2.37 (60.3)	0.19 (4.8)	1.19 (30.2)	10000 (690)
9/16	1	-HMM-H09-MN16	2.63 (66.7)	0.19 (4.8)	1.37 (34.9)	10000 (690)