


中压外螺纹转60°内锥外螺纹

Male Medium Pressure to Male Type "M"



P 中压-外	Px UNF	产品编号 Product No.	尺寸数据 in.(mm)			工作压力 Psig(bar)
			L	D	F (六角)	
1/4	9/16-18	-MNM-M04-MS9	1.52 (38.7)	0.09 (2.4)	0.63 (15.9)	20000 (1379)
1/4	3/4-16	-MNM-M04-MS12	1.69 (43.0)	0.11 (2.8)	0.75 (19.1)	20000 (1379)
1/4	7/8-14	-MNM-M04-MS14	1.90 (48.2)	0.11 (2.8)	1.00 (25.4)	20000 (1379)
1/4	1-12	-MNM-M04-MS16	1.78 (45.3)	0.11 (2.8)	1.00 (25.4)	20000 (1379)
3/8	9/16-18	-MNM-M06-MS9	1.67 (42.4)	0.09 (2.4)	0.63 (15.9)	20000 (1379)
3/8	3/4-16	-MNM-M06-MS12	1.84 (46.7)	0.20 (5.1)	0.75 (19.1)	20000 (1379)
3/8	7/8-14	-MNM-M06-MS14	2.04 (51.9)	0.15 (3.8)	1.00 (25.4)	20000 (1379)
3/8	1-12	-MNM-M06-MS16	1.93 (49.0)	0.20 (5.1)	1.00 (25.4)	20000 (1379)
9/16	9/16-18	-MNM-M09-MS9	1.95 (49.6)	0.09 (2.4)	0.94 (23.8)	20000 (1379)
9/16	3/4-16	-MNM-M09-MS12	2.08 (52.9)	0.29 (7.4)	0.94 (23.8)	20000 (1379)
9/16	7/8-14	-MNM-M09-MS14	2.23 (56.7)	0.15 (3.8)	1.00 (25.4)	20000 (1379)
9/16	1-12	-MNM-M09-MS16	2.12 (53.8)	0.31 (7.9)	1.00 (25.4)	20000 (1379)
3/4	9/16-18	-MNM-M12-MS9	2.22 (56.3)	0.09 (2.4)	1.19 (30.2)	20000 (1379)
3/4	3/4-16	-MNM-M12-MS12	2.35 (59.6)	0.29 (7.4)	1.19 (30.2)	20000 (1379)
3/4	7/8-14	-MNM-M12-MS14	2.47 (62.8)	0.15 (3.8)	1.19 (30.2)	20000 (1379)
3/4	1-12	-MNM-M12-MS16	2.36 (59.9)	0.39 (10.0)	1.19 (30.2)	20000 (1379)
3/4	1.5/16-12	-MNM-M12-MS21	2.41 (61.1)	0.44 (11.1)	1.37 (34.9)	20000 (1379)
1	9/16-18	-MNM-M16-MS9	2.77 (70.3)	0.09 (2.4)	1.50 (38.1)	20000 (1379)
1	3/4-16	-MNM-M16-MS12	2.90 (73.6)	0.29 (7.4)	1.50 (38.1)	20000 (1379)
1	7/8-14	-MNM-M16-MS14	3.02 (76.8)	0.15 (3.8)	1.50 (38.1)	20000 (1379)
1	1-12	-MNM-M16-MS16	2.91 (73.9)	0.39 (10.0)	1.50 (38.1)	20000 (1379)
1	1.5/16-12	-MNM-M16-MS21	2.89 (73.3)	0.56 (14.3)	1.50 (38.1)	20000 (1379)