



高压内螺纹转NPT外螺纹 Female High Pressure to Male NPT

P 高压接头	Px NPT	产品编号 Product No.	尺寸数据 in.(mm)			工作压力 Psig(bar)
			L	D	F (六角)	
1/4	1/8	-HFM-H04-MN2	1.19 (30.2)	0.11 (2.8)	0.75 (19.1)	15000 (1034)
1/4	1/4	-HFM-H04-MN4	1.37 (34.9)	0.11 (2.8)	0.75 (19.1)	15000 (1034)
1/4	3/8	-HFM-H04-MN6	1.37 (34.9)	0.11 (2.8)	0.75 (19.1)	15000 (1034)
1/4	1/2	-HFM-H04-MN8	1.37 (34.9)	0.11 (2.8)	0.87 (22.2)	15000 (1034)
3/8	1/4	-HFM-H06-MN4	1.50 (38.1)	0.20 (5.1)	1.00 (25.4)	15000 (1034)
3/8	3/8	-HFM-H06-MN6	1.50 (38.1)	0.20 (5.1)	1.00 (25.4)	15000 (1034)
3/8	1/2	-HFM-H06-MN8	1.75 (44.5)	0.20 (5.1)	1.00 (25.4)	15000 (1034)
9/16	3/8	-HFM-H09-MN6	1.75 (44.5)	0.31 (7.9)	1.37 (34.9)	15000 (1034)
9/16	1/2	-HFM-H09-MN8	1.94 (49.2)	0.31 (7.9)	1.37 (34.9)	15000 (1034)
9/16	3/4	-HFM-H09-MN12	2.00 (50.8)	0.31 (7.9)	1.37 (34.9)	10000 (690)
9/16	1	-HFM-H09-MN16	2.63 (66.7)	0.31 (7.9)	1.37 (34.9)	10000 (690)