



六角直通外螺纹接头 Hex Nipples

JIC 外螺纹 to JIC 外螺纹			Male JIC to Male JIC					
P NPT	Px JIC	产品编号 Product No.	尺寸数据, in(mm)					工作压力 psig(bar)
			L	F (六角)	B	Bx	E	
1/4	1/4	-MHN-AN4-AN4	1.40 (35.6)	0.50 (12.7)	0.55 (14.0)	0.55 (14.0)	0.17 (4.4)	20000 (1379)
3/8	1/4	-MHN-AN6-AN4	1.48 (37.7)	0.63 (15.9)	0.56 (14.2)	0.55 (14.0)	0.17 (4.4)	20000 (1379)
3/8	3/8	-MHN-AN6-AN6	1.49 (37.9)	0.63 (15.9)	0.56 (14.2)	0.56 (14.2)	0.23 (5.8)	20000 (1379)
1/2	3/8	-MHN-AN8-AN6	1.65 (41.8)	0.81 (20.6)	0.66 (16.7)	0.56 (14.2)	0.23 (5.8)	20000 (1379)
1/2	1/2	-MHN-AN8-AN8	1.75 (44.5)	0.81 (20.6)	0.66 (16.7)	0.66 (16.7)	0.31 (7.9)	20000 (1379)
5/8	1/2	-MHN-AN10-AN8	1.89 (48.0)	0.94 (23.8)	0.76(19.3)	0.66 (16.7)	0.31 (7.9)	20000 (1379)
5/8	5/8	-MHN-AN10-AN10	1.99 (50.6)	0.94 (23.8)	0.76(19.3)	0.76(19.3)	0.37 (9.5)	20000 (1379)
3/4	1/2	-MHN-AN12-AN8	2.07 (52.6)	1.06 (27.0)	0.86 (21.9)	0.66 (16.7)	0.31 (7.9)	15000 (1034)
3/4	5/8	-MHN-AN12-AN10	2.17 (55.1)	1.13 (28.6)	0.86 (21.9)	0.76(19.3)	0.37 (9.5)	15000 (1034)
3/4	3/4	-MHN-AN12-AN12	2.28 (57.8)	1.13 (28.6)	0.86 (21.9)	0.86 (21.9)	0.46 (11.6)	15000 (1034)
1	5/8	-MHN-AN16-AN10	2.31 (58.6)	1.37 (34.9)	0.91 (23.1)	0.76(19.3)	0.37 (9.5)	15000 (1034)
1	3/4	-MHN-AN16-AN12	2.41 (61.2)	1.37 (34.9)	0.91 (23.1)	0.86 (21.9)	0.46 (11.6)	15000 (1034)
1	1	-MHN-AN16-AN16	2.46 (62.4)	1.37 (34.9)	0.91 (23.1)	0.91 (23.1)	0.57 (14.6)	15000 (1034)