



中压外螺纹转NPT内螺纹

Male Medium Pressure to Female NPT

P 中压-外	Px NPT	产品编号 Product No.	尺寸数据 in.(mm)			工作压力 Psig(bar)
			L	D	F (六角)	
1/4	1/8	-MNM-M04-FN2	1.25 (31.8)	0.11 (2.8)	0.63 (15.9)	15000 (1034)
1/4	1/4	-MNM-M04-FN4	1.50 (38.1)	0.11 (2.8)	0.94 (23.8)	15000 (1034)
1/4	3/8	-MNM-M04-MF6	1.50 (38.1)	0.11 (2.8)	1.13 (28.6)	15000 (1034)
1/4	1/2	-MNM-M04-FN8	1.75 (44.5)	0.11 (2.8)	1.37 (34.9)	15000 (1034)
3/8	1/8	-MNM-M06-FN2	1.37 (34.9)	0.20 (5.1)	0.63 (15.9)	15000 (1034)
3/8	1/4	-MNM-M06-FN4	1.63 (41.3)	0.20 (5.1)	0.94 (23.8)	15000 (1034)
3/8	3/8	-MNM-M06-FN6	1.69 (42.9)	0.20 (5.1)	1.13 (28.6)	15000 (1034)
3/8	1/2	-MNM-M06-FN8	1.87 (47.6)	0.20 (5.1)	1.37 (34.9)	15000 (1034)
9/16	1/4	-MNM-M09-FN4	1.75 (44.5)	0.31 (7.9)	0.94 (23.8)	15000 (1034)
9/16	3/8	-MNM-M09-FN6	1.81 (46.0)	0.31 (7.9)	1.13 (28.6)	15000 (1034)
9/16	1/2	-MNM-M09-FN8	2.06 (52.4)	0.31 (7.9)	1.37 (34.9)	15000 (1034)
9/16	3/4	-MNM-M09-FN12	2.13 (54.0)	0.31 (7.9)	1.50 (38.1)	10000 (690)
3/4	1/4	-MNM-M12-FN4	1.87 (47.6)	0.41 (10.4)	1.19 (30.2)	15000 (1034)
3/4	3/8	-MNM-M12-FN6	2.00 (50.8)	0.44 (11.1)	1.19 (30.2)	15000 (1034)
3/4	1/2	-MNM-M12-FN8	2.19 (55.6)	0.44 (11.1)	1.37 (34.9)	15000 (1034)
3/4	3/4	-MNM-M12-FN12	2.31 (58.7)	0.44 (11.1)	1.50 (38.1)	10000 (690)
3/4	1	-MNM-M12-FN16	2.56 (63.5)	0.44 (11.1)	1.75 (44.5)	10000 (690)
1	1/4	-MNM-M16-FN4	2.37 (60.3)	0.41 (10.4)	1.50 (38.1)	15000 (1034)
1	3/8	-MNM-M16-FN6	2.37 (60.3)	0.56 (14.3)	1.50 (38.1)	15000 (1034)
1	1/2	-MNM-M16-FN8	2.56 (63.5)	0.56 (14.3)	1.50 (38.1)	15000 (1034)
1	3/4	-MNM-M16-FN12	2.75 (69.9)	0.56 (14.3)	1.50 (38.1)	10000 (690)
1	1	-MNM-M16-FN16	3.25 (82.6)	0.56 (14.3)	1.75 (44.5)	10000 (690)