



六角直通外螺纹接头 Hex Nipples

NPT 外螺纹 to JIC 外螺纹			Male NPT Threads to Male JIC					
P NPT	Px JIC	产品编号 Product No.	尺寸数据 in(mm)					工作压力 psig(bar)
			L	F (六角)	B	Bx	E	
1/8	1/4	-MHN-MN2-AN4	1.23 (31.3)	0.50 (12.7)	0.38 (9.7)	0.55 (14.0)	0.17 (4.4)	15000 (1034)
1/8	3/8	-MHN-MN2-AN6	1.31 (33.4)	0.63 (15.9)	0.38 (9.7)	0.56 (14.2)	0.19 (4.8)	15000 (1034)
1/4	1/4	-MHN-MN4-AN4	1.46 (37.2)	0.56 (14.3)	0.56 (14.2)	0.55 (14.0)	0.17 (4.4)	15000 (1034)
1/4	3/8	-MHN-MN4-AN6	1.49 (37.9)	0.63 (15.9)	0.56 (14.2)	0.56 (14.2)	0.23 (5.8)	15000 (1034)
1/4	1/2	-MHN-MN4-AN8	1.65 (41.9)	0.81 (20.6)	0.56 (14.2)	0.66 (16.7)	0.25 (6.4)	15000 (1034)
3/8	1/4	-MHN-MN6-AN4	1.52 (38.4)	0.69 (17.5)	0.56 (14.2)	0.55 (14.0)	0.17 (4.4)	15000 (1034)
3/8	3/8	-MHN-MN6-AN6	1.52 (38.4)	0.69 (17.5)	0.56 (14.2)	0.56 (14.2)	0.23 (5.8)	15000 (1034)
3/8	1/2	-MHN-MN6-AN8	1.62 (41.1)	0.81 (20.6)	0.56 (14.2)	0.66 (16.7)	0.31 (7.9)	15000 (1034)
1/2	1/4	-MHN-MN8-AN4	1.75 (44.5)	0.87 (22.2)	0.75 (19.1)	0.55 (14.0)	0.17 (4.4)	15000 (1034)
1/2	3/8	-MHN-MN8-AN6	1.75 (44.5)	0.87 (22.2)	0.75 (19.1)	0.56 (14.2)	0.23 (5.8)	15000 (1034)
1/2	1/2	-MHN-MN8-AN8	1.86 (47.2)	0.87 (22.2)	0.75 (19.1)	0.66 (16.7)	0.31 (7.9)	15000 (1034)
1/2	5/8	-MHN-MN8-AN10	1.98 (50.4)	0.94 (23.8)	0.75 (19.1)	0.76 (19.3)	0.37 (9.5)	15000 (1034)
3/4	1/2	-MHN-MN12-AN8	1.94 (49.4)	1.06 (27.0)	0.75 (19.1)	0.66 (16.7)	0.39 (9.9)	10000 (689)
3/4	5/8	-MHN-MN12-AN10	2.05 (52.0)	1.06 (27.0)	0.75 (19.1)	0.76 (19.3)	0.48 (12.3)	10000 (689)
3/4	3/4	-MHN-MN12-AN12	2.17 (55.1)	1.13 (28.6)	0.75 (19.1)	0.86 (21.9)	0.58 (14.8)	10000 (689)
3/4	1	-MHN-MN12-AN16	2.30 (58.4)	1.37 (34.9)	0.75 (19.1)	0.91 (23.1)	0.58 (14.8)	10000 (689)
1	3/4	-MHN-MN16-AN12	2.44 (62.0)	1.37 (34.9)	0.94 (23.9)	0.86 (21.9)	0.61 (15.5)	10000 (689)
1	1	-MHN-MN16-AN16	2.49 (63.2)	1.37 (34.9)	0.94 (23.9)	0.91 (23.1)	0.79 (20.0)	10000 (689)