


高压内螺纹转中压内螺纹

Female High Pressure to Female Medium Pressure



P 高压接头	Px 中压接头	产品编号 Product No.	尺寸数据 in.(mm)			工作压力 Psig(bar)
			L	D	F (六角)	
1/4	1/4	-HCM-H04-M04	1.37 (34.9)	0.09 (2.3)	0.75 (19.1)	20000 (1379)
1/4	3/8	-HCM-H04-M06	1.56 (39.7)	0.09 (2.3)	0.75 (19.1)	20000 (1379)
1/4	9/16	-HCM-H04-M09	1.81 (46.0)	0.09 (2.3)	1.00 (25.4)	20000 (1379)
1/4	3/4	-HCM-H04-M12	2.06 (52.4)	0.09 (2.3)	1.38 (34.9)	20000 (1379)
1/4	1	-HCM-H04-M16	2.56 (65.1)	0.09 (2.3)	1.75 (44.5)	20000 (1379)
3/8	1/4	-HCM-H06-M04	1.63 (41.3)	0.13 (3.2)	1.00 (25.4)	20000 (1379)
3/8	3/8	-HCM-H06-M06	1.81 (46.0)	0.13 (3.2)	1.00 (25.4)	20000 (1379)
3/8	9/16	-HCM-H06-M09	2.06 (52.4)	0.13 (3.2)	1.00 (25.4)	20000 (1379)
3/8	3/4	-HCM-H06-M12	2.31 (58.7)	0.13 (3.2)	1.38 (34.9)	20000 (1379)
3/8	1	-HCM-H06-M16	2.81 (71.4)	0.13 (3.2)	1.75 (44.5)	20000 (1379)
9/16	1/4	-HCM-H09-M04	1.81 (46.0)	0.19 (4.8)	1.38 (34.9)	20000 (1379)
9/16	3/8	-HCM-H09-M06	1.94 (49.2)	0.19 (4.8)	1.38 (34.9)	20000 (1379)
9/16	9/16	-HCM-H09-M09	2.25 (57.2)	0.19 (4.8)	1.38 (34.9)	20000 (1379)
9/16	3/4	-HCM-H09-M12	2.44 (61.9)	0.19 (4.8)	1.38 (34.9)	20000 (1379)
9/16	1	-HCM-H09-M16	3.00 (76.2)	0.19 (4.8)	1.75 (44.5)	20000 (1379)