


六角直通外螺纹接头

Hex Nipples

NPT 外螺纹 to ISO 直螺纹			Male NPT Threads to Male ISO Parallel Threads					
P NPT	Px BSPP	产品编号 Product No.	尺寸数据 in(mm)					工作压力 psig(bar)
			L	F (六角)	B	Bx	E	
1/8	1/4	-MHN-MN2-MG4	1.15 (29.3)	0.63 (15.9)	0.38 (9.7)	0.43 (11.0)	0.15 (3.8)	15000 (1034)
1/8	3/8	-MHN-MN2-MG6	1.25 (31.7)	0.81 (20.6)	0.38 (9.7)	0.47 (12.0)	0.19 (4.8)	15000 (1034)
1/4	1/4	-MHN-MN4-MG4	1.47 (37.4)	0.63 (15.9)	0.56 (14.2)	0.43 (11.0)	0.15 (3.8)	15000 (1034)
1/4	3/8	-MHN-MN4-MG6	1.33 (33.8)	0.81 (20.6)	0.56 (14.2)	0.47 (12.0)	0.25 (6.4)	15000 (1034)
1/4	1/2	-MHN-MN4-MG8	1.56 (39.7)	1.00 (25.4)	0.56 (14.2)	0.55 (14.0)	0.25 (6.4)	15000 (1034)
3/8	1/4	-MHN-MN6-MG4	1.35 (34.4)	0.69 (17.5)	0.56 (14.2)	0.43 (11.0)	0.15 (3.8)	15000 (1034)
3/8	3/8	-MHN-MN6-MG6	1.39 (35.4)	0.81 (20.6)	0.56 (14.2)	0.47 (12.0)	0.25 (6.4)	15000 (1034)
3/8	1/2	-MHN-MN6-MG8	1.56 (39.7)	1.00 (25.4)	0.56 (14.2)	0.55 (14.0)	0.31 (7.9)	15000 (1034)
1/2	1/4	-MHN-MN8-MG4	1.59 (40.5)	0.87 (22.2)	0.75 (19.1)	0.43 (11.0)	0.15 (3.8)	15000 (1034)
1/2	3/8	-MHN-MN8-MG6	1.63 (41.5)	0.87 (22.2)	0.75 (19.1)	0.47 (12.0)	0.25 (6.4)	15000 (1034)
1/2	1/2	-MHN-MN8-MG8	1.75 (44.5)	1.00 (25.4)	0.75 (19.1)	0.55 (14.0)	0.37 (9.5)	15000 (1034)
1/2	3/4	-MHN-MN8-MG12	1.95 (49.6)	1.25 (31.8)	0.75 (19.1)	0.63(16.0)	0.37 (9.5)	15000 (1034)
1/2	1	-MHN-MN8-MG16	2.11 (53.7)	1.50 (38.1)	0.75 (19.1)	0.75 (19.1)	0.37 (9.5)	15000 (1034)
3/4	1/2	-MHN-MN12-MG8	1.80 (45.6)	1.06 (27.0)	0.75 (19.1)	0.55 (14.0)	0.37 (9.5)	10000 (689)
3/4	3/4	-MHN-MN12-MG12	1.95 (49.6)	1.25 (31.8)	0.75 (19.1)	0.63(16.0)	0.50 (12.7)	10000 (689)
3/4	1	-MHN-MN12-MG16	2.11 (53.7)	1.50 (38.1)	0.75 (19.1)	0.75 (19.1)	0.58 (14.8)	10000 (689)
1	1/2	-MHN-MN16-MG8	2.08 (52.9)	1.37 (34.9)	0.94 (23.9)	0.55 (14.0)	0.37 (9.5)	10000 (689)
1	3/4	-MHN-MN16-MG12	2.16 (54.9)	1.37 (34.9)	0.94 (23.9)	0.63(16.0)	0.50 (12.7)	10000 (689)
1	1	-MHN-MN16-MG16	2.52 (64.0)	1.50 (38.1)	0.94 (23.9)	0.75 (19.1)	0.63 (15.9)	10000 (689)



六角直通外螺纹接头

Hex Nipples

NPT外螺纹toSAE外螺纹(O-ring)			Male NPT Threads to Male SAE O-Ring					
P NPT	Px UNF	产品编号 Product No.	尺寸数据, in.(mm)					工作压力 psig(bar)
			L	F (六角)	B	Bx	E	
1/4	7/16-20	-MHN-MN4-MS7O	1.35 (34.2)	0.56 (14.3)	0.56 (14.2)	0.43 (11.0)	0.18 (4.5)	10000 (689)
1/4	9/16-18	-MHN-MN4-MS9O	1.43 (36.4)	0.69 (17.5)	0.56 (14.2)	0.47 (12.0)	0.28 (7.1)	10000 (689)
3/8	7/16-20	-MHN-MN6-MS7O	1.39 (35.4)	0.69 (17.5)	0.56 (14.2)	0.43 (11.0)	0.18 (4.5)	10000 (689)
3/8	9/16-18	-MHN-MN6-MS9O	1.43 (36.4)	0.69 (17.5)	0.56 (14.2)	0.47 (12.0)	0.30 (7.5)	10000 (689)
3/8	3/4-16	-MHN-MN6-MS12O	1.56 (39.6)	0.87 (22.2)	0.56 (14.2)	0.55 (14.0)	0.38 (9.6)	10000 (689)
1/2	9/16-18	-MHN-MN8-MS9O	1.67 (42.5)	0.87 (22.2)	0.75 (19.1)	0.47 (12.0)	0.30 (7.5)	10000 (689)
1/2	3/4-16	-MHN-MN8-MS12O	1.75 (44.5)	0.87 (22.2)	0.75 (19.1)	0.55 (14.0)	0.39 (10.0)	10000 (689)
1/2	7/8-14	-MHN-MN8-MS14O	1.88 (47.7)	1.00 (25.4)	0.75 (19.1)	0.63 (16.0)	0.47 (11.9)	10000 (689)
3/4	9/16-18	-MHN-MN12-MS9O	1.76 (44.7)	1.06 (27.0)	0.75 (19.1)	0.47 (12.0)	0.30 (7.5)	10000 (689)
3/4	3/4-16	-MHN-MN12-MS12O	1.84 (46.7)	1.06 (27.0)	0.75 (19.1)	0.55 (14.0)	0.39 (10.0)	10000 (689)
3/4	7/8-14	-MHN-MN12-MS14O	1.92 (48.7)	1.06 (27.0)	0.75 (19.1)	0.63 (16.0)	0.49 (12.5)	10000 (689)
1	3/4-16	-MHN-MN16-MS12O	2.13 (54.1)	1.37 (34.9)	0.94 (23.9)	0.55 (14.0)	0.39 (10.0)	10000 (689)
1	7/8-14	-MHN-MN1-MS14O	2.21(56.1)	1.37 (34.9)	0.94 (23.9)	0.63 (16.0)	0.49 (12.5)	10000 (689)