



内螺纹弯头
Female Elbows

NPT 内螺纹			Female NPT Threads			
P NPT	产品编号 Product No.	尺寸数据, in(mm)				工作压力 psig(bar)
		L	F (厚度)	B	E	
1/8	-MHF-MN2	0.75 (19.1)	0.63 (15.9)	0.41 (10.4)	0.31 (8.0)	15000 (1034)
1/4	-MHF-MN4	1.00 (25.4)	0.75 (19.1)	0.59 (15.0)	0.41 (10.4)	15000 (1034)
3/8	-MHF-MN6	1.20 (30.6)	1.00 (25.4)	0.59 (15.0)	0.54 (13.8)	15000 (1034)
1/2	-MHF-MN8	1.50 (38.1)	1.37 (34.9)	0.78 (19.8)	0.67 (17.0)	15000 (1034)
3/4	-MHF-MN12	1.50 (38.1)	1.50 (38.1)	0.81 (20.6)	0.88 (22.3)	10000 (689)
1	-MHF-MN16	1.91 (48.5)	1.75 (44.5)	1.00 (25.4)	1.11 (28.2)	10000 (689)

ISO 锥管内螺纹			Female ISO Tapered Pipe Threads			
P BSPT	产品编号 Product No.	尺寸数据, in(mm)				工作压力 psig(bar)
		L	F (厚度)	B	E	
1/8	-MHF-MR2	0.75 (19.1)	0.63 (15.9)	0.41 (10.4)	0.31 (8.0)	15000 (1034)
1/4	-MHF-MR4	1.00 (25.4)	0.75 (19.1)	0.59 (15.0)	0.41 (10.4)	15000 (1034)
3/8	-MHF-MR6	1.20 (30.6)	1.00 (25.4)	0.59 (15.0)	0.54 (13.8)	15000 (1034)
1/2	-MHF-MR8	1.50 (38.1)	1.37 (34.9)	0.78 (19.8)	0.67 (17.0)	15000 (1034)
3/4	-MHF-MR12	1.50 (38.1)	1.50 (38.1)	0.81 (20.6)	0.88 (22.3)	10000 (689)
1	-MHF-MR16	1.91 (48.5)	1.75 (44.5)	1.00 (25.4)	1.11 (28.2)	10000 (689)