

R23 系列中等流量不锈钢减压阀

(R23 Series Medium Flow Stainless Steel Regulator)

R23系列不锈钢减压阀,采用大面积金属膜片结构,输出压力稳定,灵敏度高,主要用于中等流量气体系统。

R23 series stainless steel pressure reducing valve adopts large-area metal diaphragm structure, stable output pressure and high sensitivity, mainly used for medium flow gas system.



产品特点 Features

- ◎ 结构紧凑,大流量
- ◎ 膜片与本体之间采用金属密封
- ◎ 输出压力稳定
- ◎ 金属膜片确保输出稳定性及使用寿命
- ◎ 多种出口压力范围
- ◎ 可选择面板安装
- ◎ Compact structure, large flow
- ◎ Metal seal is used between the diaphragm and the body
- ◎ The output pressure is stable
- ◎ Metal diaphragm ensures output stability and service life
- ◎ Various outlet pressure ranges
- ◎ Optional panel mounting

特性参数 Operating Parameters

- ◎ 进出气接口:3/4"NPT
- ◎ 最大进口压力:500/3500Psi
- ◎ 输出压力范围:0-290Psi
- ◎ 工作温度:-40至74°C
- ◎ 泄漏率:1*10-8atm.cc/sec He
- ◎ CV值:1.6
- ◎ Air inlet and outlet interface: 3/4" NPT
- ◎ Max inlet pressure: 500/3500Psi
- ◎ Output pressure range: 0-290Psi
- ◎ Working temperature: -40~74°C
- ◎ Leak rate: 1*10-8atm.cc/sec He
- ◎ CV value: 1.6

◎ 材质:

阀体:316L
阀芯:316L.
阀座:PTFE/PCTFE
其余部件:304

◎ Material:

Valve body: 316L
Spool: 316L.
Valve seat: PTFE/PCTFE
Rest of the parts: 304

订购指南 Ordering Information

系列 Series	阀座材料 Valve seat material	进口压力 Import pressure	出口压力 Outlet pressure	进气接口 Intake port	出气接口 Air outlet	选项 Options
R23	P	A	C	00	00	P
	P:PTFE C:PCTFE	A:500psi B:3500psi	D:50psi E:150psi F:200psi	00:3/4NPT (F) 01:3/4NPT(M) 11:3/4卡套接头 12:20MM卡套接头 其他接头可选	00:3/4NPT (F) 01:3/4NPT(M) 11:3/4卡套接头 12:20MM卡套接头 其他接头可选	P:带面板安装