



高压外螺纹转60°内锥外螺纹
Male High Pressure to Male Type "M"

P 高压接头	Px UNF	产品编号 Product No.	尺寸数据 in.(mm)			工作压力 Psig(bar)
			L	D	F (六角)	
1/4	9/16-18	-HMM-H04-MS9	1.46 (37.1)	0.09 (2.3)	0.63 (15.9)	60000 (4137)
1/4	3/4-16	-HMM-H04-MS12	1.63 (41.4)	0.09 (2.3)	0.75 (19.1)	30000 (2058)
1/4	7/8-14	-HMM-H04-MS14	1.83 (46.6)	0.09 (2.3)	1.00 (25.4)	50000 (3447)
1/4	1-12	-HMM-H04-MS16	1.72 (43.7)	0.09 (2.3)	1.00 (25.4)	30000 (2058)
3/8	9/16-18	-HMM-H06-MS9	1.77 (44.9)	0.09 (2.3)	0.81 (20.6)	60000 (4137)
3/8	3/4-16	-HMM-H06-MS12	1.90 (48.2)	0.13 (3.2)	0.81 (20.6)	30000 (2058)
3/8	7/8-14	-HMM-H06-MS14	2.09 (53.1)	0.13 (3.2)	1.00 (25.4)	50000 (3447)
3/8	1-12	-HMM-H06-MS16	1.97 (50.1)	0.13 (3.2)	1.00 (25.4)	30000 (2058)
3/8	1.5/16-12	-HMM-H06-MS21	2.09 (53.1)	0.13 (3.2)	1.38 (34.9)	20000 (1379)
9/16	9/16-18	-HMM-H09-MS9	2.07 (52.6)	0.09 (2.3)	1.19 (30.2)	60000 (4137)
9/16	3/4-16	-HMM-H09-MS12	2.20 (55.9)	0.19 (4.8)	1.19 (30.2)	30000 (2058)
9/16	7/8-14	-HMM-H09-MS14	2.33 (59.1)	0.15 (3.8)	1.19 (30.2)	50000 (3447)
9/16	1-12	-HMM-M09-MS16	2.21 (56.2)	0.19 (4.8)	1.19 (30.2)	30000 (2058)
9/16	1.5/16-12	-HMM-M09-MS21	2.26 (57.4)	0.19 (4.8)	1.38 (34.9)	20000 (1379)