


中压内螺纹转60°内锥外螺纹

Female Medium Pressure to Male Type "M"



P 中压接头	Px UNF	产品编号 Product No.	尺寸数据 in.(mm)			工作压力 Psig(bar)
			L	D	F (六角)	
1/4	9/16-18	-MTM-M04-MS9	1.19 (30.2)	0.09 (2.3)	0.63 (15.9)	20000 (1379)
1/4	3/4-16	-MTM-M04-MS12	1.31 (33.3)	0.11 (2.8)	0.75 (19.1)	20000 (1379)
1/4	7/8-14	-MTM-M04-MS14	1.50 (38.1)	0.11 (2.8)	1.00 (25.4)	20000 (1379)
3/8	9/16-18	-MTM-M06-MS9	1.37 (34.9)	0.09 (2.3)	0.75 (19.1)	20000 (1379)
3/8	3/4-16	-MTM-M06-MS12	1.50 (38.1)	0.09 (2.3)	0.75 (19.1)	20000 (1379)
3/8	7/8-14	-MTM-M06-MS14	1.75 (44.5)	0.15 (3.8)	1.00 (25.4)	20000 (1379)
9/16	9/16-18	-MTM-M09-MS9	1.69 (42.9)	0.09 (2.3)	1.00 (25.4)	20000 (1379)
9/16	3/4-16	-MTM-M09-MS12	1.81 (46.0)	0.29 (7.4)	1.00 (25.4)	20000 (1379)
9/16	7/8-14	-MTM-M09-MS14	1.94 (49.2)	0.15 (3.8)	1.00 (25.4)	20000 (1379)
9/16	1-12	-MTM-M09-MS16	1.81 (46.0)	0.31 (7.9)	1.00 (25.4)	20000 (1379)
3/4	7/8-14	-MTM-M12-MS14	2.19 (55.6)	0.15 (3.8)	1.38 (34.9)	20000 (1379)
3/4	1-12	-MTM-M12-MS16	2.13 (54.0)	0.39 (10.4)	1.38 (34.9)	20000 (1379)
3/4	1.5/16-12	-MTM-M12-MS21	2.00 (50.8)	0.44 (11.1)	1.38 (34.9)	20000 (1379)
1	1.5/16-12	-MTM-M16-MS21	2.56 (65.1)	0.56 (14.3)	1.75 (44.5)	20000 (1379)