



中压外螺纹转中压外螺纹

Male Medium Pressure to Male Medium Pressure

P 中压-外	Px 中压-外	产品编号 Product No.	尺寸数据 in.(mm)			工作压力 Psig(bar)
			L	D	F (六角)	
1/4	1/4	-MNM-M04-M04	1.63 (41.3)	0.11 (2.8)	0.50 (12.7)	20000 (1379)
3/8	1/4	-MNM-M06-M04	1.87 (47.6)	0.11 (2.8)	0.63 (15.9)	20000 (1379)
3/8	3/8	-MNM-M06-M06	2.00 (50.8)	0.20 (5.1)	0.63 (15.9)	20000 (1379)
9/16	1/4	-MNM-M09-M04	2.13 (54.0)	0.11 (2.8)	0.94 (23.8)	20000 (1379)
9/16	3/8	-MNM-M09-M06	2.31 (58.7)	0.20 (5.1)	0.94 (23.8)	20000 (1379)
9/16	9/16	-MNM-M09-M09	2.50 (63.5)	0.31 (7.9)	0.94 (23.8)	20000 (1379)
3/4	1/4	-MNM-M12-M04	2.44 (61.9)	0.11 (2.8)	1.19 (30.2)	20000 (1379)
3/4	3/8	-MNM-M12-M06	2.56 (66.1)	0.20 (5.1)	1.19 (30.2)	20000 (1379)
3/4	9/16	-MNM-M12-M09	2.75 (69.9)	0.31 (7.9)	1.19 (30.2)	20000 (1379)
3/4	3/4	-MNM-M12-M12	2.94 (74.6)	0.44 (11.1)	1.19 (30.2)	20000 (1379)
1	1/4	-MNM-M16-M04	3.00 (76.2)	0.11 (2.8)	1.50 (38.1)	20000 (1379)
1	3/8	-MNM-M16-M06	3.13 (79.4)	0.20 (5.1)	1.50 (38.1)	20000 (1379)
1	9/16	-MNM-M16-M09	3.31 (84.2)	0.31 (7.9)	1.50 (38.1)	20000 (1379)
1	3/4	-MNM-M16-M12	3.44 (87.4)	0.44 (11.1)	1.50 (38.1)	20000 (1379)
1	1	-MNM-M16-M16	3.94 (100.2)	0.56 (14.3)	1.50 (38.1)	20000 (1379)