


六角直通外螺纹接头

Hex Nipples



NPT 外螺纹 to 60°内锥外螺纹			Male NPT Threads to Male Type "M"					
P NPT	Px UNF	产品编号 Product No.	尺寸数据 in(mm)					工作压力 psig(bar)
			L	F (六角)	B	Bx	E	
1/8	9/16-18	-MHN-MN2-MS9	1.22 (31.0)	0.63 (15.9)	0.38 (9.7)	0.50 (12.7)	0.09 (2.4)	15000 (1034)
1/8	3/4-16	-MHN-MN2-MS12	1.39 (35.3)	0.75 (19.1)	0.38 (9.7)	0.63 (16.0)	0.19 (4.8)	15000 (1034)
1/4	9/16-18	-MHN-MN4-MS9	1.40 (35.5)	0.63 (15.9)	0.56 (14.2)	0.50 (12.7)	0.09 (2.4)	15000 (1034)
1/4	3/4-16	-MHN-MN4-MS12	1.57 (39.8)	0.75 (19.1)	0.56 (14.2)	0.63 (16.0)	0.25 (6.4)	15000 (1034)
1/4	7/8-14	-MHN-MN6-MS14	1.77 (45.0)	1.00 (25.4)	0.56 (14.2)	0.76 (19.2)	0.15 (3.8)	15000 (1034)
3/8	9/16-18	-MHN-MN6-MS9	1.42 (36.1)	0.69 (17.5)	0.56 (14.2)	0.50 (12.7)	0.09 (2.4)	15000 (1034)
3/8	3/4-16	-MHN-MN6-MS12	1.57 (39.8)	0.75 (19.1)	0.56 (14.2)	0.63 (16.0)	0.29 (7.4)	15000 (1034)
3/8	7/8-14	-MHN-MN6-MS14	1.77 (45.0)	1.00 (25.4)	0.56 (14.2)	0.76 (19.2)	0.15 (3.8)	15000 (1034)
1/2	9/16-18	-MHN-MN8-MS9	1.66 (42.2)	0.87 (22.2)	0.75 (19.1)	0.50 (12.7)	0.09 (2.4)	15000 (1034)
1/2	3/4-16	-MHN-MN8-MS12	1.79 (45.5)	0.87 (22.2)	0.75 (19.1)	0.63 (16.0)	0.29 (7.4)	15000 (1034)
1/2	7/8-14	-MHN-MN8-MS14	1.96 (49.9)	1.00 (25.4)	0.75 (19.1)	0.76 (19.2)	0.15 (3.8)	15000 (1034)
1/2	1-12	-MHN-MN8-MS16	1.85 (47.0)	1.00 (25.4)	0.75 (19.1)	0.64 (16.3)	0.38 (9.6)	15000 (1034)
3/4	9/16-18	-MHN-MN12-MS9	1.75 (44.5)	1.06 (27.0)	0.75 (19.1)	0.50 (12.7)	0.09 (2.4)	10000 (689)
3/4	3/4-16	-MHN-MN12-MS12	1.88 (50.9)	1.06 (27.0)	0.75 (19.1)	0.63 (16.0)	0.29 (7.4)	10000 (689)
3/4	7/8-14	-MHN-MN12-MS14	2.00 (50.8)	1.06 (27.0)	0.75 (19.1)	0.76 (19.2)	0.15 (3.8)	10000 (689)
3/4	1-12	MHN-MN12-MS16	2.00 (50.8)	1.06 (27.0)	0.75 (19.1)	0.64 (16.3)	0.39 (10.0)	10000 (689)
1	1-12	-MHN-MN16-MS16	2.18 (55.4)	1.37 (34.9)	0.94 (23.9)	0.64 (16.3)	0.39 (10.0)	10000 (689)
1	1.5/16-12	-MHN-MN1-MS21	2.16 (54.8)	1.37 (34.9)	0.94 (23.9)	0.62 (15.8)	0.69 (17.5)	10000 (689)