


六角直通外螺纹接头

Hex Nipples



NPT 外螺纹

Male NPT Threads

P NPT	Px NPT	产品编号 Product No.	尺寸数据, in(mm)					工作压力 psig(bar)
			L	F (六角)	B	Bx	E	
1/8	1/8	-MHN-MN2	1.05 (26.6)	0.44 (11.1)	0.38 (9.7)	0.38 (9.7)	0.19 (4.8)	15000 (1034)
1/4	1/8	-MHN-MN4-MN2	1.30 (32.9)	0.56 (14.3)	0.56 (14.2)	0.38 (9.7)	0.19 (4.8)	15000 (1034)
1/4	1/4	-MHN-MN4	1.47 (37.4)	0.56 (14.3)	0.56 (14.2)	0.56 (14.2)	0.25 (6.4)	15000 (1034)
3/8	1/8	-MHN-MN6-MN2	1.34 (34.1)	0.69 (17.5)	0.56 (14.2)	0.38 (9.7)	0.19 (4.8)	15000 (1034)
3/8	1/4	-MHN-MN6-MN4	1.52 (38.6)	0.69 (17.5)	0.56 (14.2)	0.56 (14.2)	0.25 (6.4)	15000 (1034)
3/8	3/8	-MHN-MN6	1.52 (38.6)	0.69 (17.5)	0.56 (14.2)	0.56 (14.2)	0.31 (7.9)	15000 (1034)
1/2	1/8	-MHN-MN8-MN2	1.58 (40.2)	0.87 (22.2)	0.75 (19.1)	0.38 (9.7)	0.19 (4.8)	15000 (1034)
1/2	1/4	-MHN-MN8-MN4	1.76 (44.7)	0.87 (22.2)	0.75 (19.1)	0.56 (14.2)	0.25 (6.4)	15000 (1034)
1/2	3/8	-MHN-MN8-MN6	1.76 (44.7)	0.87 (22.2)	0.75 (19.1)	0.56 (14.2)	0.31 (7.9)	15000 (1034)
1/2	1/2	-MHN-MN8	1.95 (49.6)	0.87 (22.2)	0.75 (19.1)	0.75 (19.1)	0.38 (9.6)	15000 (1034)
3/4	1/8	-MHN-MN12-MN2	1.67 (42.4)	1.06 (27.0)	0.75 (19.1)	0.38 (9.7)	0.19 (4.8)	10000 (689)
3/4	1/4	-MHN-MN12-MN4	1.85 (46.9)	1.06 (27.0)	0.75 (19.1)	0.56 (14.2)	0.25 (6.4)	10000 (689)
3/4	3/8	-MHN-MN12-MN6	1.85 (46.9)	1.06 (27.0)	0.75 (19.1)	0.56 (14.2)	0.31 (7.9)	10000 (689)
3/4	1/2	-MHN-MN12-MN8	2.04 (51.8)	1.06 (27.0)	0.75 (19.1)	0.75 (19.1)	0.38 (9.6)	10000 (689)
3/4	3/4	-MHN-MN12	2.04 (51.8)	1.06 (27.0)	0.75 (19.1)	0.75 (19.1)	0.58 (14.8)	10000 (689)
1	1/8	-MHN-MN16-MN2	1.96 (49.8)	1.37 (34.9)	0.94 (23.9)	0.38 (9.7)	0.19 (4.8)	10000 (689)
1	1/4	-MHN-MN16-MN4	2.14 (54.3)	1.37 (34.9)	0.94 (23.9)	0.56 (14.2)	0.25 (6.4)	10000 (689)
1	3/8	-MHN-MN16-MN6	2.14 (54.3)	1.37 (34.9)	0.94 (23.9)	0.56 (14.2)	0.31 (7.9)	10000 (689)
1	1/2	-MHN-MN16-MN8	2.33 (59.2)	1.37 (34.9)	0.94 (23.9)	0.75 (19.1)	0.38 (9.6)	10000 (689)
1	3/4	-MHN-MN16-MN12	2.33 (59.2)	1.37 (34.9)	0.94 (23.9)	0.75 (19.1)	0.58 (14.8)	10000 (689)
1	1	-MHN-MN16	2.52 (64.0)	1.37 (34.9)	0.94 (23.9)	0.94 (23.9)	0.79 (20.0)	10000 (689)

ISO 锥管外螺纹

Male ISO Tapered Threads

P BSPT	Px BSPT	产品编号 Product No.	尺寸数据, in(mm)					工作压力 psig(bar)
			L	F (六角)	B	Bx	E	
1/8	1/8	-MHN-MR2	1.05 (26.6)	0.44 (11.1)	0.38 (9.7)	0.38 (9.7)	0.19 (4.8)	15000 (1034)
1/4	1/8	-MHN-MR4-MR2	1.30 (32.9)	0.56 (14.3)	0.56 (14.2)	0.38 (9.7)	0.19 (4.8)	15000 (1034)
1/4	1/4	-MHN-MR4	1.47 (37.4)	0.56 (14.3)	0.56 (14.2)	0.56 (14.2)	0.25 (6.4)	15000 (1034)
3/8	1/8	-MHN-MR6-MR2	1.34 (34.1)	0.69 (17.5)	0.56 (14.2)	0.38 (9.7)	0.19 (4.8)	15000 (1034)
3/8	1/4	-MHN-MR6-MR4	1.52 (38.6)	0.69 (17.5)	0.56 (14.2)	0.56 (14.2)	0.25 (6.4)	15000 (1034)
3/8	3/8	-MHN-MR6	1.52 (38.6)	0.69 (17.5)	0.56 (14.2)	0.56 (14.2)	0.31 (7.9)	15000 (1034)
1/2	1/4	-MHN-MR8-MR4	1.76 (44.7)	0.87 (22.2)	0.75 (19.1)	0.56 (14.2)	0.25 (6.4)	15000 (1034)
1/2	3/8	-MHN-MR8-MR6	1.76 (44.7)	0.87 (22.2)	0.75 (19.1)	0.56 (14.2)	0.31 (7.9)	15000 (1034)
1/2	1/2	-MHN-MR8	1.95 (49.6)	0.87 (22.2)	0.75 (19.1)	0.75 (19.1)	0.38 (9.6)	15000 (1034)
3/4	1/4	-MHN-MR12-MR4	1.85 (46.9)	1.06 (27.0)	0.75 (19.1)	0.56 (14.2)	0.25 (6.4)	10000 (689)
3/4	3/8	-MHN-MR12-MR6	1.85 (46.9)	1.06 (27.0)	0.75 (19.1)	0.56 (14.2)	0.31 (7.9)	10000 (689)
3/4	1/2	-MHN-MR12-MR8	2.04 (51.8)	1.06 (27.0)	0.75 (19.1)	0.75 (19.1)	0.38 (9.6)	10000 (689)
3/4	3/4	-MHN-MR12	2.04 (51.8)	1.06 (27.0)	0.75 (19.1)	0.75 (19.1)	0.58 (14.8)	10000 (689)
1	1/4	-MHN-MR16-MR4	2.14 (54.3)	1.37 (34.9)	0.94 (23.9)	0.56 (14.2)	0.25 (6.4)	10000 (689)
1	1/2	-MHN-MR16-MR8	2.33 (59.2)	1.37 (34.9)	0.94 (23.9)	0.75 (19.1)	0.38 (9.6)	10000 (689)
1	3/4	-MHN-MR16-MR12	2.33 (59.2)	1.37 (34.9)	0.94 (23.9)	0.75 (19.1)	0.58 (14.8)	10000 (689)
1	1	-MHN-MR16	2.52 (64.0)	1.37 (34.9)	0.94 (23.9)	0.94 (23.9)	0.79 (20.0)	10000 (689)