



中压内螺纹转中压外螺纹

Female Medium Pressure to Male Medium Pressure

P 中压-内	Px 中压-外	产品编号 Product No.	尺寸数据 in.(mm)			工作压力 Psig(bar)
			L	D	F (六角)	
1/4	1/4	-MTM-M04-M04	1.37 (34.9)	0.11 (2.8)	0.63 (15.9)	20000 (1379)
1/4	3/8	-MTM-M04-M06	1.50 (38.1)	0.11 (2.8)	0.63 (15.9)	20000 (1379)
1/4	9/16	-MTM-M04-M09	1.63 (41.3)	0.11 (2.8)	0.94 (23.8)	20000 (1379)
3/8	1/4	-MTM-M06-M04	1.69 (42.9)	0.11 (2.8)	0.75 (19.1)	20000 (1379)
3/8	3/8	-MTM-M06-M06	1.69 (42.9)	0.20 (5.1)	0.75 (19.1)	20000 (1379)
3/8	9/16	-MTM-M06-M09	1.87 (47.6)	0.20 (5.1)	0.94 (23.8)	20000 (1379)
3/8	3/4	-MTM-M06-M12	2.37 (60.3)	0.20 (5.1)	1.19 (30.2)	20000 (1379)
9/16	1/4	-MTM-M09-M04	1.94 (49.2)	0.11 (2.8)	1.00 (25.4)	20000 (1379)
9/16	3/8	-MTM-M09-M06	2.06 (52.4)	0.20 (5.1)	1.00 (25.4)	20000 (1379)
9/16	9/16	-MTM-M09-M09	2.13 (54.0)	0.31 (7.9)	1.00 (25.4)	20000 (1379)
9/16	3/4	-MTM-M09-M12	2.25 (57.2)	0.31 (7.9)	1.19 (30.2)	20000 (1379)
9/16	1	-MTM-M09-M16	2.50 (63.5)	0.31 (7.9)	1.50 (38.1)	20000 (1379)
3/4	1/4	-MTM-M12-M04	2.19 (55.6)	0.11 (2.8)	1.38 (34.9)	20000 (1379)
3/4	3/8	-MTM-M12-M06	2.31 (58.7)	0.20 (5.1)	1.38 (34.9)	20000 (1379)
3/4	9/16	-MTM-M12-M09	2.44 (61.9)	0.31 (7.9)	1.38 (34.9)	20000 (1379)
3/4	3/4	-MTM-M12-M12	2.56 (66.1)	0.44 (11.1)	1.50 (38.1)	20000 (1379)
3/4	1	-MTM-M12-M16	2.94 (74.6)	0.44 (11.1)	1.50 (38.1)	20000 (1379)
1	9/16	-MTM-M16-M09	3.06 (77.8)	0.31 (7.9)	1.75 (44.5)	20000 (1379)
1	3/4	-MTM-M16-M12	3.19 (81.0)	0.44 (11.1)	1.75 (44.5)	20000 (1379)
1	1	-MTM-M16-M16	3.50 (88.9)	0.56 (14.3)	1.75 (44.5)	20000 (1379)