


## 中压内螺纹转NPT内螺纹

Female Medium Pressure to Male Medium Pressure



| P<br>中压接头 | Px<br>NPT | 产品编号<br>Product No. | 尺寸数据 in.(mm) |             |             | 工作压力<br>Psig(bar) |
|-----------|-----------|---------------------|--------------|-------------|-------------|-------------------|
|           |           |                     | L            | D           | F (六角)      |                   |
| 1/4       | 1/8       | -MTF-M04-FN2        | 1.37 (34.9)  | 0.11 (2.8)  | 0.63 (15.9) | 15000 (1034)      |
| 1/4       | 1/4       | -MTF-M04-FN4        | 1.63 (41.3)  | 0.11 (2.8)  | 0.94 (23.8) | 15000 (1034)      |
| 1/4       | 3/8       | -MTF-M04-FN6        | 1.63 (41.3)  | 0.11 (2.8)  | 1.13 (28.6) | 15000 (1034)      |
| 1/4       | 1/2       | -MTF-M04-FN8        | 2.00 (50.8)  | 0.11 (2.8)  | 1.38 (34.9) | 15000 (1034)      |
| 3/8       | 1/8       | -MTF-M06-FN2        | 1.50 (38.1)  | 0.20 (5.1)  | 0.75 (19.1) | 15000 (1034)      |
| 3/8       | 1/4       | -MTF-M06-FN4        | 1.75 (44.5)  | 0.20 (5.1)  | 0.94 (23.8) | 15000 (1034)      |
| 3/8       | 3/8       | -MTF-M06-FN6        | 1.81 (46.0)  | 0.20 (5.1)  | 1.13 (28.6) | 15000 (1034)      |
| 3/8       | 1/2       | -MTF-M06-FN8        | 2.13 (54.0)  | 0.20 (5.1)  | 1.38 (34.9) | 15000 (1034)      |
| 3/8       | 3/4       | -MTF-M06-FN12       | 2.25 (57.2)  | 0.20 (5.1)  | 1.50 (38.1) | 10000 (690)       |
| 9/16      | 1/8       | -MTF-M09-FN2        | 1.63 (41.3)  | 0.31 (7.9)  | 1.00 (25.4) | 15000 (1034)      |
| 9/16      | 1/4       | -MTF-M09-FN4        | 2.00 (50.8)  | 0.31 (7.9)  | 1.00 (25.4) | 15000 (1034)      |
| 9/16      | 3/8       | -MTF-M09-FN6        | 2.00 (50.8)  | 0.31 (7.9)  | 1.13 (28.6) | 15000 (1034)      |
| 9/16      | 1/2       | -MTF-M09-FN8        | 2.25 (57.2)  | 0.31 (7.9)  | 1.38 (34.9) | 15000 (1034)      |
| 9/16      | 3/4       | -MTF-M09-FN12       | 2.25 (57.2)  | 0.31 (7.9)  | 1.50 (38.1) | 10000 (690)       |
| 9/16      | 1         | -MTF-M09-FN16       | 2.63 (66.7)  | 0.31 (7.9)  | 1.75 (44.5) | 10000 (690)       |
| 3/4       | 1/4       | -MTF-M12-FN4        | 2.00 (50.8)  | 0.41 (10.4) | 1.38 (34.9) | 15000 (1034)      |
| 3/4       | 3/8       | -MTF-M12-FN6        | 2.37 (60.3)  | 0.44 (11.1) | 1.38 (34.9) | 15000 (1034)      |
| 3/4       | 1/2       | -MTF-M12-FN8        | 2.63 (66.7)  | 0.44 (11.1) | 1.38 (34.9) | 15000 (1034)      |
| 3/4       | 3/4       | -MTF-M12-FN12       | 2.63 (66.7)  | 0.44 (11.1) | 1.50 (38.1) | 10000 (690)       |
| 3/4       | 1         | -MTF-M12-FN16       | 2.63 (66.7)  | 0.44 (11.1) | 1.75 (44.5) | 10000 (690)       |
| 1         | 1/4       | -MTF-M16-FN4        | 2.37 (60.3)  | 0.41 (10.4) | 1.75 (44.5) | 15000 (1034)      |
| 1         | 3/8       | -MTF-M16-FN6        | 2.50 (63.5)  | 0.55 (13.9) | 1.75 (44.5) | 15000 (1034)      |
| 1         | 1/2       | -MTF-M16-FN8        | 3.00 (76.2)  | 0.56 (14.3) | 1.75 (44.5) | 15000 (1034)      |
| 1         | 3/4       | -MTF-M16-FN12       | 3.00 (76.2)  | 0.56 (14.3) | 1.75 (44.5) | 10000 (690)       |
| 1         | 1         | -MTF-M16-FN16       | 3.00 (76.2)  | 0.56 (14.3) | 1.75 (44.5) | 10000 (690)       |