


外螺纹四通

Male Branch Tees



NPT 外螺纹

Male NPT Threads

P NPT	产品编号 Product No.	尺寸数据, in(mm)				工作压力 psig(bar)
		L	F (厚度)	B	E	
1/8	-MXC-MN2	0.75 (19.1)	0.44 (11.1)	0.38 (9.7)	0.19 (4.8)	15000 (1034)
1/4	-MXC-MN4	1.00 (25.4)	0.56 (14.3)	0.56 (14.2)	0.25 (6.4)	15000 (1034)
3/8	-MXC-MN6	1.10 (28.0)	0.69 (17.5)	0.56 (14.2)	0.31 (7.9)	15000 (1034)
1/2	-MXC-MN8	1.44 (36.6)	0.87 (22.2)	0.75 (19.1)	0.38 (9.6)	15000 (1034)
3/4	-MXC-MN12	1.56 (39.6)	1.06 (27.0)	0.75 (19.1)	0.58 (14.8)	10000 (689)
1	-MXC-MN16	1.89 (48.0)	1.37 (34.9)	0.94 (23.9)	0.79 (20.0)	10000 (689)

ISO 锥管外螺纹

Male ISO Tapered Pipe Threads

P BSPT	产品编号 Product No.	尺寸数据, in(mm)				工作压力 psig(bar)
		L	F (厚度)	B	E	
1/8	-MXC-MR2	0.75 (19.1)	0.44 (11.1)	0.38 (9.7)	0.19 (4.8)	15000 (1034)
1/4	-MXC-MR4	1.00 (25.4)	0.56 (14.3)	0.56 (14.2)	0.25 (6.4)	15000 (1034)
3/8	-MXC-MR6	1.10 (28.0)	0.69 (17.5)	0.56 (14.2)	0.31 (7.9)	15000 (1034)
1/2	-MXC-MR8	1.44 (36.6)	0.87 (22.2)	0.75 (19.1)	0.38 (9.6)	15000 (1034)
3/4	-MXC-MR12	1.56 (39.6)	1.06 (27.0)	0.75 (19.1)	0.58 (14.8)	10000 (689)
1	-MXC-MR16	1.89 (48.0)	1.37 (34.9)	0.94 (23.9)	0.79 (20.0)	10000 (689)