



内外螺纹接头 Adapters

ISO 平行螺纹-活接			Female/Male ISO Parallel Threads						
P BSPP	Px BSPP	产品编号 Product No.	尺寸数据, in(mm)						工作压力 psig(bar)
			L	F (六角)	H (六角)	B	Bx	E	
1/4	1/4	-MDP-MFG4-MG4	1.42 (36.0)	0.63 (15.9)	0.63 (15.9)	0.18 (4.5)	0.43 (11.0)	0.15 (3.8)	10000 (689)
1/4	3/8	-MDP-MFG4-MG6	1.54 (39.0)	0.81 (20.6)	0.81 (20.6)	0.18 (4.5)	0.47 (12.0)	0.19 (4.7)	10000 (689)
1/4	1/2	-MDP-MFG4-MG8	1.62 (41.2)	1.00 (25.4)	0.63 (15.9)	0.18 (4.5)	0.55 (14.0)	0.19 (4.7)	10000 (689)
3/8	1/4	-MDP-MFG6-MG4	1.57 (40.0)	0.81 (20.6)	0.63 (15.9)	0.25 (6.4)	0.43 (11.0)	0.15 (3.8)	10000 (689)
3/8	3/8	-MDP-MFG6-MG6	1.61 (41.0)	0.81 (20.6)	0.81 (20.6)	0.25 (6.4)	0.47 (12.0)	0.25 (6.4)	10000 (689)
3/8	1/2	-MDP-MFG6-MG8	1.75 (44.5)	1.00 (25.4)	0.81 (20.6)	0.25 (6.4)	0.55 (14.0)	0.31 (7.9)	10000 (689)
1/2	1/2	-MDP-MFG8-MG8	1.82 (46.2)	1.00 (25.4)	0.81 (20.6)	0.28 (7.0)	0.55 (14.0)	0.37 (9.5)	10000 (689)
1/2	3/4	-MDP-MFG8-MG12	1.98 (50.2)	1.25 (31.8)	1.00 (25.4)	0.28 (7.0)	0.63(16.0)	0.44 (11.1)	10000 (689)
3/4	1/2	-MDP-MFG12-MG8	2.02 (51.2)	1.25 (31.8)	1.00 (25.4)	0.35 (9.0)	0.55 (14.0)	0.37 (9.5)	10000 (689)
3/4	3/4	-MDP-MFG12-MG12	2.19 (55.5)	1.25 (31.8)	1.37 (34.9)	0.35 (9.0)	0.63(16.0)	0.50 (12.7)	10000 (689)
3/4	1	-MDP-MFG12-MG16	2.34 (59.5)	1.50 (38.1)	1.37 (34.9)	0.35 (9.0)	0.75 (19.1)	0.63 (15.9)	10000 (689)
1	3/4	-MDP-MFG16-MG12	2.50 (63.5)	1.50 (38.1)	1.75 (44.5)	0.43 (9.8)	0.63(16.0)	0.50 (12.7)	10000 (689)
1	1	-MDP-MFG16-MG16	2.62 (66.5)	1.50 (38.1)	1.75 (44.5)	0.43 (9.8)	0.75 (19.1)	0.63 (15.9)	10000 (689)