

T15系列 /T15 Series

- ◎ 材质: 316/316L、高级-316/316L
- ◎ 最大工作压力: 1034 bar(15,000psig)
- ◎ 工作温度: -198°C 至 537°C (-325 F 至1000°F)
- ◎ 退火无缝管
- ◎ 常规供货长度: 1m、2m、3m、6 m、40 in、80 in、10 ft、20 ft,
- ◎ 可根据客户实际规格定制长度
- ◎ Materials:316/316L,enhanced-316/316L
- ◎ Working pressures: up to 15,000 psig (1034 bar)
- ◎ Working temperature:-325°F to 1000°F (-198°C to 537°C)
- ◎ Annealed seamless tubing
- ◎ Standard length: 40 in, 80 in, 10 ft, 20 ft, 1 m, 2 m, 3 m and 6 m
- ◎ Customized length as per customer requirement is also available

常温工作压力 Working Pressure at Ambient Temperature

外径 in.	壁厚 in.	工作压力 bar (psig)
1/8	0.037	1,034 (15,000)
1/4	0.083	1,034 (15,000)
	0.065	710 (10,300)
3/8	0.118	1,034 (15,000)
	0.095	690 (10,000)
1/2	0.156	1,034 (15,000)
	0.134	772 (11,200)
3/4	0.240	1,034 (15,000)
	0.188	690 (10,000)
1	0.220	690 (10,000)

订购信息/Ordering Information

外径 in.	壁厚 in.	订购号 ^{①②}	
1/8	0.037	□□-T15-2-037-6M	□□-T15-2-037-20F
1/4	0.083	□□-T15-4-083-6M	□□-T15-4-083-20F
	0.065	□□-T15-4-065-6M	□□-T15-4-065-20F
3/8	0.118	□□-T15-6-118-6M	□□-T15-6-118-20F
	0.095	□□-T15-6-095-6M	□□-T15-6-095-20F
1/2	0.156	□□-T15-8-156-6M	□□-T15-8-156-20F
	0.134	□□-T15-8-134-6M	□□-T15-8-134-20F
3/4	0.240	□□-T15-12-240-6M	□□-T15-12-240-20F
	0.188	□□-T15-12-188-6M	□□-T15-12-188-20F
1	0.220	□□-T15-16-220-6M	□□-T15-16-220-20F

① 型号中的 6M 表示管子单根长度为 6 m, 20F 表示管子单根长度为 20 ft.

② 在订购号中添加材料代码以获得完整的订购号: 316/316L的代码为SS, 高级-316/316L的代码为SH.

③ In the ordering number, "6M" designator refers to 6 m tubing length and "20F" designator refers to 20 ft tubing length.

④ To order, add the material designator as prefix: SS for 316/316L and SH for enhanced-316/316L.