

## R68 系列超大流量不锈钢减压器

(R68 series ultra-large flow stainless steel pressure reducer)

R68系列不锈钢减压器,采用超大面积塑料膜片,输出压力精准,流量大,适用于超大流量场合

R68 series stainless steel pressure reducer adopts large area plastic diaphragm, which has accurate output pressure and large flow rate, which is suitable for large flow rate occasion



### 产品特点 Features

- ◎ 大面积塑料膜片
- ◎ 超大流量
- ◎ 精确调节,出口压力范围大
- ◎ 多种负载选择
- ◎ 多种进出接头可选择
- ◎ Large area plastic film
- ◎ Large flow
- ◎ Precise adjustment, large outlet pressure range
- ◎ Various load options
- ◎ Various in and out connectors for selection

### 特性参数 Operating Parameters

- ◎ 进出气接口:2"法兰、螺纹等
  - ◎ 最大进口压力:150/350Psi
  - ◎ 输出压力范围:0-50, 0-100Psi
  - ◎ 工作温度:-40至74°C
  - ◎ CV值:10.0
  - ◎ Air inlet and outlet interface: 2" flanges, threads, etc.
  - ◎ Max inlet pressure: 150/350Psi
  - ◎ Output pressure range: 0-50, 0-100Psi
  - ◎ Working temperature: -40~74°C
  - ◎ CV value: 10.0
- ◎ 材质:
- 阀体:316L  
阀芯:316L.  
阀座:PCTFE  
其余部件:304
- ◎ Material:
- Valve body: 316L  
Spool: 316L.  
Valve seat: PCTFE  
Rest of the parts: 304

### 订购指南 Ordering Information

系列 Series	阀座材料 Valve seat material	进口压力 Import pressure	出口压力 Outlet pressure	进气接口 Intake port	出气接口 Airoutlet	选项 Options
<b>R68</b>	<b>P</b>	<b>A</b>	<b>C</b>	<b>00</b>	<b>00</b>	<b>P</b>
	P:PTFE V:VTION	A:150psi B:350psi	C:50psi D:100psi	00:2"NPT(F) 01:2"焊接 11:2"法兰 其他接头可选	00:2"NPT(F) 01:2"焊接 11:2"法兰 其他接头可选	